

# FIXING ANCHOR W-FAZ/A4, W-FAZ/HCR

02.6

**Anchor dimensions: Fixing anchor W-FAZ/A4, A4 stainless steel with large washer**  
 (dia. x thickness of washer **M8: 24 x 2**  
**M10: 30 x 2,5**  
**M12: 37 x 3**  
**M16: 50 x 3)**



Description	Anchor dia.	Standard anchoring depth			Reduced anchoring depth			Overall length L [mm]	Wrench size [mm]	Approval ETA	Art. No.	P. Qty.
		Attachment height t <sub>fix</sub> [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h <sub>ef</sub> [mm]	Attachment height t <sub>fix</sub> [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h <sub>ef</sub> [mm]					
<b>W-FAZ/A4 with large washer</b>	M8	10	8 x 60	46	21	8 x 49	35	75	13	ETA-99/0011	5928 508 010*	100
		15			26			80			5928 508 015*	100
		30			41			95			5928 508 030*	100
		50			61			115			5928 508 050*	100
	M10	10	10 x 75	60	30	10 x 55	40	90	17		5928 510 010*	50
		15			35			95			5928 510 015*	50
		30			50			110			5928 510 030*	50
		50			70			130			5928 510 050*	50
	M12	15	12 x 90	70	35	12 x 70	50	110	19		5928 512 015*	25
		30			50			125			5928 512 030*	25
		50			70			145			5928 512 050*	25
		160			-			-			255	5928 112 005*
	M16	25	16 x 110	85	45	16 x 90	65	145	24		5928 516 025*	25

\* S-24 cannot be ordered.