

FIXING ANCHOR W-FAZ/A4, W-FAZ/HCR

02.6

Anchor dimensions: W-FAZ/HCR fixing anchor (HCR highly corrosion-resistant steel):



Description	Anchor dia.	Standard anchoring depth			Reduced anchoring depth			Overall length L [mm]	Wrench size [mm]	Approval ETA	Art. No.	P. Qty.
		Attachment height t _{fix} [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h _{ef} [mm]	Attachment height t _{fix} [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h _{ef} [mm]					
W-FAZ/ HCR	M8	-	-	-	11	8 x 49	35	65	13	ETA-99/0011	5928 658 011 *	100
		10	8 x 60	46	21			75			5928 608 010 *	100
		15			26			80			5928 608 015 *	100
		30			41			95			5928 608 030 *	100
		50			61			115			5928 608 050 *	100
		-			-			-			10	10 x 55
	10	10 x 75	60	30	90	5928 610 010 *	50					
	15			35	95	5928 610 015 *	50					
	30			50	110	5928 610 030 *	50					
	50			70	130	5928 610 050 *	50					
	M12	-	-	-	10	12 x 70	50	85	19		5928 652 010 *	25
		15	12 x 90	70	35			110			5928 612 015 *	25
		20			40			115			5928 612 020 *	25
		30			50			125			5928 612 030 *	25
		50			70			145			5928 612 050 *	25
		25			16 x 110			85			45	16 x 90
	50	70	170	5928 616 050 *		20						
	100	-	-	220		5928 016 100 *	10					
	M20	30	20 x 125	100	-	-	-	165	30		5928 620 030 *	10

* S-24 cannot be ordered.