

FIXING ANCHOR WITH FEMALE THREAD W-FAZ-IG/A4 – W-FAZ-IG/HCR

02.8

Anchor dimensions: Fixing anchor W-FAZ-IG/A4, stainless steel A4 Cotter-pin mounting



Description	Anchor dia.	Attachment height Type S t _{fix} [mm]	Attachment height Type SK t _{fix} [mm]	Total length L [mm]	Drill bit nominal dia. d ₀ [mm]	Drill hole depth h ₁ ≥ [mm]	Approval ETA	Art. No.	P./Qty.
W-FAZ-IG/A4 Cotter-pin mounting	M6	4-12	6-14	50	8	60	ETA-99/0011	0904 806 110*	100
	M8	2-8	9-15	62	10	75		0904 808 110	50
	M10	15-19	8-11	70	12	90		0904 810 110	25
	M12	16-21	9-14	86	16	105		0904 812 110	20

Anchor dimensions: Fixing anchor W-FAZ-IG/A4, stainless steel A4 Through-bolt mounting



Description	Anchor dia.	Attachment height Type S t _{fix} [mm]	Attachment height Type SK t _{fix} [mm]	Total length L [mm]	Drill bit nominal dia. d ₀ [mm]	Drill hole depth h ₁ ≥ [mm]	Approval ETA	Art. No.	P./Qty.
W-FAZ-IG/A4 Through-bolt mounting	M6	10	14	60	8	60	ETA-99/0011	0904 806 011*	100
		20	24	70				0904 806 012*	
		30	34	80				0904 806 013*	
	M8	10	15	72	10	75		0904 808 011	50
		20	25	82				0904 808 012*	
		30	35	92				0904 808 013*	
	M10	10	16	80	12	90		0904 810 011	25
		20	26	90				0904 810 012	
		30	36	100				0904 810 013*	
	M12	10	17	96	16	105		0904 812 011	20
		20	27	106				0904 812 012*	
		30	37	116				0904 812 013*	

Setting tool for cotter-pin mounting

Setting tool must leave behind a visible marking on the concrete surface



for anchor diameter	Art. No.	P./Qty.
M6	0904 706 150*	1
M8	0904 708 150	
M10	0904 710 150	
M12	0904 712 150	

Setting tool for through-bolt mounting

The stop of the setting tool must rest on attached part



for anchor diameter	Art. No.	P./Qty.
M6	0904 706 050*	1
M8	0904 708 050	
M10	0904 710 050	
M12	0904 712 050	

* S-24 cannot be ordered.