

W-FAZ/S FIXING ANCHOR

02.5

Anchor dimensions: Fixing anchor W-FAZ/S, galvanized steel with large washer
 (dia. x thickness of washer **M8: 24 x 2**
M10: 30 x 2.5
M12: 37 x 3
M16: 50 x 3)



| Description | Anchor dia. | Standard anchoring depth | | | Reduced anchoring depth | | | Overall length L [mm] | Wrench size [mm] | Approval ETA | Art. No. | P. Qty. |
|----------------------------------|-------------|---|------------------------------|--|---|------------------------------|--|-----------------------|------------------|---------------|---------------|---------|
| | | Attachment height t _{fix} [mm] | Drill hole dia. x depth [mm] | Effective anchoring depth h _{ef} [mm] | Attachment height t _{fix} [mm] | Drill hole dia. x depth [mm] | Effective anchoring depth h _{ef} [mm] | | | | | |
| W-FAZ/S with large washer | M8 | 10 | 8 x 60 | 46 | 21 | 8 x 49 | 35 | 75 | 13 | ETA-99/0011 | 5928 308 010* | 100 |
| | | 15 | | | 26 | | | 80 | | | 5928 308 015* | 100 |
| | | 30 | | | 41 | | | 95 | | | 5928 308 030* | 100 |
| | M10 | 10 | 10 x 75 | 60 | 30 | 10 x 55 | 40 | 90 | 17 | | 5928 310 010* | 50 |
| | | 15 | | | 35 | | | 95 | | | 5928 310 015* | 50 |
| | | 30 | | | 50 | | | 110 | | | 5928 310 030* | 50 |
| | | 50 | | | 70 | | | 130 | | | 5928 310 050* | 50 |
| | | 100 | | | 120 | | | 180 | | | 5928 310 100* | 50 |
| | M12 | 15 | 12 x 90 | 70 | 35 | 12 x 70 | 50 | 110 | 19 | | 5928 312 015* | 25 |
| | | 30 | | | 125 | | | 5928 312 030* | | | 25 | |
| | | 50 | | | 145 | | | 5928 312 050* | | | 25 | |
| | | 105 | | | 200 | | | 5928 312 105 | | | 25 | |
| | | 125 | | | - | - | 220 | 0904 531 212 | | 25 | | |
| | | 145 | | | - | - | 240 | 0904 531 213 | | 20 | | |
| | | 160 | | | - | - | 255 | 0904 531 214 | | 20 | | |
| | | 190 | | | - | - | 285 | 0904 531 215 | | 20 | | |
| | M16 | 25 | 16 x 110 | 85 | 45 | 16 x 90 | 65 | 145 | 24 | 5928 316 025* | 20 | |
| | | 50 | | | 70 | | | 170 | | 5928 316 050* | 20 | |

* S-24 cannot be ordered.

Anchor dimensions: W-FAZ/S fixing anchor, galvanized steel with large washer as per DIN EN ISO 7094 (DIN 440)
 (dia. x thickness of washer **M12: 44 x 4**
M16 56 x 5)



| Description | Anchor dia. | Standard anchoring depth | | | Reduced anchoring depth | | | Overall length L [mm] | Wrench size [mm] | Approval ETA | Art. No. | P. Qty. | |
|---|-------------|---|------------------------------|--|---|------------------------------|--|-----------------------|------------------|--------------|--------------|---------------|----|
| | | Attachment height t _{fix} [mm] | Drill hole dia. x depth [mm] | Effective anchoring depth h _{ef} [mm] | Attachment height t _{fix} [mm] | Drill hole dia. x depth [mm] | Effective anchoring depth h _{ef} [mm] | | | | | | |
| W-FAZ/S with large washer as per DIN EN ISO 7094 (DIN 440) | M12 | 105 | 12 x 90 | 70 | 125 | 12 x 70 | 50 | 200 | 19 | ETA-99/0011 | 5928 362 105 | 25 | |
| | | 125 | | | - | | | - | | | 220 | 0904 531 222 | 25 |
| | | 145 | | | - | | | - | | | 240 | 0904 531 223 | 20 |
| | | 160 | | | - | | | - | | | 255 | 0904 531 224 | 20 |
| | | 190 | | | - | | | - | | | 285 | 0904 531 225 | 20 |
| | | 230 | | | - | | | - | | | 325 | 5928 362 230* | 20 |
| | | 260 | | | - | | | - | | | 355 | 5928 362 260* | 20 |
| | M16 | 100 | 16 x 110 | 85 | - | - | - | 220 | 24 | | 0904 531 622 | 10 | |
| | | 140 | | | - | | | - | | | 260 | 0904 531 623 | 10 |
| | | 180 | | | - | | | - | | | 300 | 0904 531 624 | 10 |

* S-24 cannot be ordered.