

FIXING ANCHOR W-FAZ/A4, W-FAZ/HCR

02.6

Anchor dimensions: Fixing anchor W-FAZ/A4, stainless steel A4



Description	Anchor dia.	Standard anchoring depth			Reduced anchoring depth			Overall length L [mm]	Wrench size [mm]	Approval ETA	Art. No.	P. Qty.		
		Attachment height t _{fix} [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h _{ef} [mm]	Attachment height t _{fix} [mm]	Drill hole dia. x depth [mm]	Effective anchoring depth h _{ef} [mm]							
W-FAZ/A4	M8	-	-	-	11	8 x 49	35	65	13	ETA-99/0011	5928 458 011	100		
		10	8 x 60	46	21			75			5928 408 010	100		
		15			26			80			5928 408 015	100		
		30			41			95			5928 408 030	100		
		50			61			115			5928 408 050	100		
		100			111			165			5928 408 100	50		
	M10	-			-	-	10	10 x 55	40		70	17	5928 451 010	50
		-	-	-	20	80	5928 451 020				50			
		10	10 x 75	60	30	90	5928 410 010				50			
		15			35	95	5928 410 015				50			
		20			40	100	5928 410 020*				50			
		30			50	110	5928 410 030				50			
		50			70	130	5928 410 050				50			
		75			95	155	5928 410 075				50			
		100			120	180	5928 410 100				50			
		M12			-	-	-				10		12 x 70	50
	-				-	-	20	95	5928 452 020		25			
	15				12 x 90	70	35	110	5928 412 015		25			
	20		40	115			5928 412 020	25						
	30		50	125			5928 412 030	25						
	50		70	145			5928 412 050	25						
	65		85	160			5928 412 065	25						
	85		105	180			5928 412 085	25						
	105		125	200			5928 412 105	25						
	125		-	-			-	220	0904 621 206		25			
	160		-	-			-	255	0904 621 207		20			
	180		-	-			-	275	0904 621 208		20			
	190		-	-			-	285	0904 621 209*		20			
	205		-	-			-	300	0904 621 210		20			
	230	-	-	-			325	0904 621 211	20					
	M16	-	-	-			15	16 x 90	65		115	24	5928 456 015	20
		5	16 x 110	85	25	125	5928 416 005				20			
		15			35	135	5928 416 015				20			
		25			45	145	5928 416 025				20			
		50			70	170	5928 416 050				20			
		80			100	200	5928 416 080				10			
		100			-	-	-				220		0904 616 100	10
		160			-	-	-				280		0904 616 160	10
		180			-	-	-				300		0904 616 180	10
		205			-	-	-				325		0904 616 205	10
		220			-	-	-				340		0904 616 220	10
		M20			30	20 x 125	100				-		-	-
	60				-			-	-		195	5928 420 060	10	
	130		-	-	-			265	0904 620 130		5			
	150		-	-	-			285	0904 620 150		5			
	M24	30	24 x 155	125	-	-	-	200	36		0904 624 030*	10		
		60			-	-	-	230			0904 624 060*	5		
		75			-	-	-	245			0904 624 075*	5		

* S-24 cannot be ordered.