

W-BS CONCRETE SCREW

01.3

W-BS/S concrete screw, galvanized steel with hexagon head and pressed-on washer, Type S



Washer diameter:	
Size	Screw dia. [mm]
5	12.5
6	15
8	16
10	20
12	23
14	28

Anchor size	Attachment height t_{fix} [mm]			Total length L [mm]	Length of the anchor in the concrete h_{nom} [mm]			Drill bit nominal dia d_0 [mm]	Drill hole depth h_1 [mm]			Wrench size [mm]	Art. No.	P. Qty.	
	$t_{fix 1}$	$t_{fix 2}$	$t_{fix 3}$		h_{nom1}	h_{nom2}	h_{nom3}		$H_{1.1}$	$H_{1.2}$	$H_{1.3}$				
5	5	-	-	40	35	-	-	5	40	-	-	10	5929 125 005	100	
	15	-	-	50											5929 125 015
	25	-	-	60											5929 125 025
6	5	-	-	40	35	-	-	6	40	-	-	13	5929 126 005	100	
	15	10	-	50											5929 126 015
	25	20	5	60											5929 126 025
	45	40	25	80											5929 126 045
	65	60	45	100											5929 126 065
8	5	-	-	50	45	-	-	8	55	-	-	13	5929 128 005	50	
	15	5	-	60											5929 128 015
	25	15	5	70											5929 128 025
	35	25	15	80											5929 128 035
	45	35	25	90											5929 128 045
	55	45	35	100											5929 128 055
	75	65	55	120											5929 128 075
	95	85	75	140											5929 128 095
	115	105	95	160											5929 128 115
10	5	-	-	60	55	-	-	10	65	-	-	15	5929 121 005	25	
	25	5	-	80											5929 121 025
	35	15	5	90											5929 121 035
	45	25	15	100											5929 121 045
	65	45	35	120											5929 121 065
	85	65	55	140											5929 121 085
	105	85	75	160											5929 121 105
12	15	-	-	80	65	-	-	12	75	-	-	17	5929 122 015	25	
	45	25	10	110											5929 122 045
14	5	-	-	80	75	-	-	14	85	-	-	21	5929 124 005	25	
	35	10	-	110											5929 124 035
	55	30	15	130											5929 124 055