

WIT-PM 200

25.2

Anchoring in masonry (solid and perforated brick)

Masonry: Sieve sleeves




Designation	Nom. drill dia. d_0 [mm]	Drill hole depth h_0 [mm]	Anchoring depth h_{ef} [mm]	Suitable for anchor rod	Approval ETA	Art. No.	P. Qty.
SH 12 x 80	12	85	80	M8	ETA-13/0037	0903 44 123	20
SH 16 x 85	16	90	85	M10		0903 44 164	
SH 16 x 130	16	135	130	M10		0903 44 165	
SH 20 x 85	20	90	85	M12 and M16		0903 44 203	

Masonry: Pass-through sieve sleeve




Designation	Nom. drill dia. d_0 [mm]	Drill hole depth h_0 [mm]	Anchoring depth h_{ef} [mm]	Suitable for anchor rod	Approval ETA	Art. No.	P. Qty.
SH 16 x 130/200	16	340	130	M10	ETA-13/0037	0903 44 163	10

Masonry: Anchor rods



Dia- meter	Processed without sieve sleeve			Processed with sieve sleeve			Suitable for sieve sleeve	Galvanized steel Steel quality: 5.8 Art. No.	Stainless steel A4-70 Art. No.	P. Qty.
	Nom. drill dia. d_0 [mm]	Anchoring depth h_{ef} [mm]	Drill hole depth h_0 [mm]	Nom. drill dia. d_0 [mm]	Anchoring depth h_{ef} [mm]	Drill hole depth h_0 [mm]				
M8	10	80	80	12	80	85	SH 12 x 80	5916 008 999	5916 108 999	10
M10	12	90	90	16	85 130 130	90 135 135 + t_{fix}	SH 16 x 85; SH 16 x 130; SH 16 x 130/200	5916 010 999	5916 110 999	
M12	14	100	100	20	85	90	SH 20 x 85	5916 012 999	5916 112 999	
M16	18	100	100	20	85	90	SH 20 x 85	5916 016 999	5916 116 999	

Masonry: Cleaning accessories



For diameter		Nom. drill dia. d_0 [mm]	Cleaning Brush Art. No.	Handle Art. No.	Machine Mounting Art. No.	Blow-Out Pump Art. No.	P. Qty.
M8	Without sieve sleeve	10	0905 499 021	0905 499 103	Hexagon: 0905 499 101 SDS plus: 0905 499 102	0903 990 001	1
	With SH 12 Sieve Sleeve	12	0905 499 022				
M10	Without sieve sleeve	12	0905 499 022				
	With SH 16 Sieve Sleeve	16	0905 499 025				
M12	Without sieve sleeve	14	0905 499 023				
	With SH 20 Sieve Sleeve	20	0905 499 026				
M16	Without sieve sleeve	18	0905 499 024				
	With SH 20 Sieve Sleeve	20	0905 499 026				