

WIT-PM 200

25.2

Anchoring in uncracked concrete

Uncracked concrete: Anchor rods, galvanized steel 5.8 and A4-70 stainless steel



Dia- meter	Fastening height t_{fix} [mm]	Total length L [in mm]	Effective anchoring depth h_{ef} [mm]	Nom. drill dia. d_0 [mm]	Drill hole depth $h_0 \geq$ [mm]	ETA approval	Galvanized steel Steel quality: 5.8 Art. No.	Stainless steel A4-70 Art. No.	P. Qty.
M8	20	110	80	10	80	ETA- 12/0569	5915 108 110	5915 208 110	10
	60	150					5915 108 150	5915 208 150	
	-	1,000					5916 008 999	5916 108 999	
M10	15	115	90	12	90		5915 110 115	5915 210 115	
	30	130					5915 110 130	5915 210 130	
	65	165					5915 110 165	5915 210 165	
	90	190					5915 110 190	5915 210 190	
	-	1,000					5916 010 999	5916 110 999	
	-	-					-	-	
M12	10	135	110	14	110		5915 112 135	5915 212 135	
	35	160					5915 112 160	5915 212 160	
	85	210					5915 112 210	5915 212 210	
	125	250					5915 112 250	5915 212 250	
	175	300					5915 112 300	5915 212 300	
	-	1,000					5916 012 999	5916 112 999	
M16	20	165	125	18	125		5915 116 165	5915 216 165	
	45	190					5915 116 190	5915 216 190	
	85	230					5915 116 230	5915 216 230	
	105	250					5915 116 250	5915 216 250	
	155	300					5915 116 300	5915 216 300	
	-	1,000					5916 016 999	5916 116 999	
M20	20	220	170	24	170		5915 120 220	5915 220 220	
	60	260					5915 120 260	5915 220 260	
	100	300					5915 120 300	5915 220 300	
	-	1,000				5916 020 999	5916 120 999		
M24	15	260	210	28	210	5915 124 260	5915 224 260	5	
	55	300				5915 124 300	5915 224 300		
	-	1,000				5916 024 999	5916 124 999		

Uncracked concrete: Cleaning accessories



For diameter	Nom. drill dia. d_0 [mm]	Cleaning Brush Art. No.	Extension Art. No.	Machine Mounting Art. No.	Blow-Out Pump Art. No.	P. Qty.
M8	10	0905 499 001	0905 499 111	Hexagon: 0905 499 101 SDS plus: 0905 499 102	0903 990 001	1
M10	12	0905 499 002				
M12	14	0905 499 003				
M16	18	0905 499 004				
M20	24	0905 499 005				
M24	28	0905 499 008				

Würth system components

