

WIT-P 200

25.2

WIT-P 200 injection mortar: Masonry (perforated and solid brick), uncracked concrete		
WIT-P 200 mortar cartridge	Art. No.	Mortar cartridge, 330 ml (incl. 1 static mixer) 5918 200 330P P. Qty. 1/12 Mortar cartridge, 150 ml (incl. 1 static mixer and press-out piston) 5918 201,150 P. Qty. 1/12
Application Gun	Art. No. P. Qty. = 1	Application Gun: 0891 003 HandyMax®: 0891 007
Static mixer	Art. No. P. Qty. = 10	0903 420 001
Extension for static mixer	Art. No. P. Qty. = 10	0903 420 004

Masonry (perforated and solid brick): WIT-P 200 + WIT-AS anchor bar or WIT-IG internal screw thread sleeve												
Anchor diameter	WIT-AS Anchor Bar						WIT-IG Internal Screw Thread Sleeve					
	M8		M10		M12		M6		M8			
Plastic sieve sleeve	Without WIT-SH	WIT-SH 18/95	Without WIT-SH	WIT-SH 18/95	Without WIT-SH	WIT-SH 18/95	Without WIT-SH	WIT-SH 18/95	Without WIT-SH	WIT-SH 18/95	Without WIT-SH	WIT-SH 18/95
Nom. drill dia.	d ₀ [in mm]											
Drill hole depth	h ₀ ≥ [in mm]											
Installation depth of sieve sleeve	h _{nom} = [in mm]											
Effective anchoring depth	h _{ef} [in mm]											
Torque while installing anchor	T _{inst} = [in Nm]											
Anchor diameter	WIT-AS Anchor Bar						Female thread WIT-IG					
	M8		M10		M12		M6		M8			
Total length	l [in mm]											
Max. attachment height	f _{fix} [in mm]											
Anchor Bar	Art. No. P. Qty. = 10											
WIT-AS, galvanized steel	0903 451 081	0903 452 081	0903 451 082	0903 452 082	0903 451 083	0903 452 083	0903 451 101	0903 452 101	0903 451 102	0903 452 102	0903 451 103	0903 452 103
WIT-AS A4, stainless steel A4	0903 451 081	0903 452 081	0903 451 082	0903 452 082	0903 451 083	0903 452 083	0903 451 101	0903 452 101	0903 451 102	0903 452 102	0903 451 103	0903 452 103
Internal screw thread sleeve	Art. No. P. Qty. = 10											
WIT-AS, galvanized steel	0903 451 121	0903 452 121	0903 451 122	0903 452 122	0903 451 123	0903 452 123	0903 451 124	0903 452 124	0903 461 061	0903 462 061	0903 461 081	0903 462 081
WIT-AS A4, stainless steel A4	0903 451 121	0903 452 121	0903 451 122	0903 452 122	0903 451 123	0903 452 123	0903 451 124	0903 452 124	0903 461 061	0903 462 061	0903 461 081	0903 462 081
Plastic sieve sleeve WIT-SH 18/95	Art. No. P. Qty. = 10 0903 44 180											
Cleaning drilled hole	Art. No. P. Qty. = 1											
Cleaning Brush (steel)	Perforated stone: Anchoring with sieve sleeve WIT-SH 18/95						M8/M10/M12			0905 499 024		
	Solid stone: Anchoring without sieve sleeve WIT-SH 18/95						M8:			0905 499 021		
							M10:			0905 499 022		
Handle	Art. No. P. Qty. = 1 0905 499 103						M12:			0905 499 023		
	Art. No. P. Qty. = 1 0903 990 001											

Uncracked concrete: WIT-P 200 + anchor bar W-VI-A/S or W-VI-A/A4											
Anchor diameter	M8		M10		M12		M16		M20		M24
Nom. drill dia.	d ₀ [in mm]										
Drilling hole depth / anchoring depth	h ₀ / hef [in mm]										
Torque while installing anchor	T _{inst} = [in Nm]										
Total length	l [in mm]										
Max. attachment height	f _{fix} [in mm]										
Anchor bar W-VI-A/S	Art. No.										
Galvanized steel 5.8,	5915 108 110	5915 108 150	5915 110 115	5915 110 130	5915 110 165	5915 110 190	5915 112 135	5915 112 160	5915 112 210	5915 112 250	5915 112 300
Anchor bar W-VI-A/A4	Art. No.										
Stainless steel A4-70	5915 208 110	5915 208 150	5915 210 115	5915 210 130	5915 210 165	5915 210 190	5915 212 135	5915 212 160	5915 212 210	5915 212 250	5915 212 300
Packing unit	P. Qty.										
Cleaning Brush (steel)	Art. No. P. Qty. = 1										
Machine Mount	Art. No. P. Qty. = 1										
Brush template	Art. No. P. Qty. = 1										
Blow-Out Pump/ Compressed-Air Nozzle	Art. No. P. Qty. = 1										
designed for Art. No. 0714 92 13	Blow-Out Pump: 0903 990 001									Compressed air nozzle ¹⁾ : 0905 499 201	

¹⁾ Compressed air nozzle designed for blow-out gun Art. No. 0714 92 13

²⁾ 2 Nm for anchor plate on anchoring base that does not make contact.

*HandyMax[®] is a registered trademark of SORATON SA

Würth system components

