

W-UR 14 SYMCON® GS SCAFFOLD ANCHOR

44.1

Screw dimensions plus recommended transverse load: **W-GS SymCon Scaffold Eye Screw**, galvanized steel, strength class 6.8



Designation	Screw diameter d_s [mm]	Screw length l_s [mm]	Art. No.	P. Qty.	Suitable plastic anchor	Recommended transverse load parallel to facade V_{rec} [kN]
W-GS SymCon 10 x 125	10	125	0160 810 001	25	W-UR 14x110	0.75
W-GS SymCon 10 x 190		190	0160 810 003		W-UR 14x110, 14x140, 14x180	0.29
W-GS SymCon 10 x 260		260	0160 810 005			0.18
W-GS SymCon 10 x 330		330	0160 810 006		-	

Anchor dimensions: **W-UR 14 Plastic Frame-Fixing Anchor**



Designation	Attachment height (plaster, insulation etc.) t_{fix} [mm]	Anchor length L [mm]	Setting depth h_{nom} [mm]	Nom. drill dia. d_0 [mm]	Drilled hole depth h_1 [mm]	Art. No.	P. Qty.
W-UR 14 x 110	10	110	100	14	110 (+ t_{fix})	0912 814 002	25
W-UR 14 x 140	40	140				0912 814 003	
W-UR 14 x 180	80	180				0912 814 005	

W-UR 14 SymCon GS = W-GS 10 SymCon Scaffold Eye Screw + W-UR 14 Plastic Frame-Fixing Anchor



Scaffold eye screw	Plastic frame-fixing dowel	ETA for multiple attachment	Attachment height (plaster, insulation etc.) t_{fix} [mm]	Setting depth h_{nom} [mm]	Nom. drill dia. d_0 [mm]	Drilled hole depth h_1 [mm]	Art. No.	P. Qty.
W-GS SymCon 10 x 125	W-UR 14 x 110	ETA-11/0309	10	100	14	110 (+ t_{fix})	0912 814 012	25
W-GS SymCon 10 x 190	W-UR 14 x 110	ETA-11/0309	10				0912 814 032	
	W-UR 14 x 140 ¹⁾	-	40				0912 814 033 ²⁾	1 ²⁾
	W-UR 14 x 180 ¹⁾	-	80				0912 814 035 ²⁾	
W-GS SymCon 10 x 260	W-UR 14 x 110	ETA-11/0309	10				0912 814 052	25
	W-UR 14 x 140 ¹⁾	-	40				0912 814 053 ²⁾	1 ²⁾
	W-UR 14 x 180 ¹⁾	-	80				0912 814 055 ²⁾	
W-GS SymCon 10 x 330	W-UR 14 x 110	ETA-11/0309	10				0912 814 062	25
	W-UR 14 x 140 ¹⁾	-	40				0912 814 063 ²⁾	1 ²⁾
	W-UR 14 x 180 ¹⁾	-	80				0912 814 065 ²⁾	

¹⁾No approval given, as the screw and anchor are not packaged and supplied as an attachment unit (e.g. anchor and screw together in one package).

²⁾Item includes 25x W-UR 14 Frame-Fixing Anchors and 25x W-GS 10 SymCon Threaded Eye Screws.

W-UR F 14 x 110 Plastic Frame-Fixing Anchor + M12 x 16 connection thread, size 19



Designation	ETA for multiple attachment	Attachment height (plaster, insulation etc.) t_{fix} [mm]	Setting depth h_{nom} [mm]	Nom. drill dia. d_0 [mm]	Drilled hole depth h_1 [mm]	Art. No.	P. Qty.	
W-UR F 14 SymCon, M12 x 16 mm (anchor + screw)	Size 19	ETA-11/0309	10	100	14	110 (+ t_{fix})	0912 814 202	20
W-UR F 14x110 (without screw)	-	-	10	100	14	110 (+ t_{fix})	0912 814 102	20