

W-GS GYPSUM PLASTERBOARD ANCHORS

73

Performance data					
Anchor type		Type Z	Type Z/L	Type K	
Recommended tensile load	Gypsum plasterboard $d \geq 12.5$ mm	$F_{rec.}$ [kN]	0.1	0.1	0.1
	Gypsum plasterboard $d \geq 25$ mm		0.1	0.12	0.1
	Gypsum fibrous panels		0.12	0.12	-
Recommended transverse load	Gypsum plasterboard $d \geq 12.5$ mm	$F_{rec.}$ [kN]	0.12	0.12	0.12
	Gypsum plasterboard $d \geq 25$ mm		0.15	0.15	0.12
	Gypsum fibrous panels		0.15	0.15	-

Characteristic values				
Axial spacing	$a \geq$ [mm]	100		
Edge spacing	$a_{r \geq}$ [mm]	50		
Minimum component thickness	$d \geq$ [mm]	9.5		
Thread dia. of screw	$d_{thr.}$ [mm]	4.5	4.5	4.5 - 5
Hole dia. in comp.	$d_{comp.}$ [mm]	6.5		

Anchor dimensions				
Total length	l [mm]	33	39	33
Max. attachment height	d_a [mm]	Depends on screw length		
Designation		W-GS type Z	W-GS type Z/L	W-GS type K
Art. No.		0903 252	0903 253	0903 251
Packing unit	P. Qty.	200		

Storable in [®]ORSY

Würth system components

