

## CAR BULBS, 12 V

### Economical

#### Bulbs for instrument lighting and switches



Fig.	Model designation	Volts	Watts	Base type	Art. No.	P. Qty.
A	-	12	1.2	W2 x 4,6d	<b>0720 160 1</b>	10
B	-	12	2	W2 x 4,6d	<b>0720 160 5</b>	10
C	Clear	12	0.36	W2 x 4,6d	<b>0720 162 4</b>	10
D	W3W	12	3	W2, 1 x 9,5d	<b>0720 161 1</b>	10
E	-	12	2	BA9s	<b>0720 151 1</b>	10
F	T4W	12	4	BA9s	<b>0720 150 1</b>	10
G	-	12	4	BA9s	<b>0720 152 1</b>	10
H	-	12	3	BA7s	<b>0720 155 1</b>	10

### Soffit Bulbs



Model designation	Volts	Watts	Dimensions in mm			Base designation	Art. No.	P. Qty.
			Length A	Glass bulb width B	Contact C			
Test bulbs soffits	12	3	21 (+/-1)	6.2 (+/-1)	3.5	SV 7 - 8	<b>0720 177 1</b>	10
-	12	3	27 (+/-1)	8.2 max.	3.5	SV 7 - 8	<b>0720 170 1</b>	10
C5W	12	5	35 (+/-1)	11 max.	3.5	SV 8.5 - 8	<b>0720 171 1</b>	10
C5W Daylight	12	5	35 (+/-1)	11 max.	3.5	SV 8.5 - 8	<b>0720 171 16</b>	10
-	12	5	40 (+/-1)	11 max.	3.5	SV 8.5 - 8	<b>0720 172 1</b>	10
-	12	6	31 (+/-2)	6.0 (+/-0.5)	3.5	SV 8.5 - 8	<b>0720 171 10</b>	10
Japanese version	12	10	31 (+/-2)	10 (+/-0.5)	3.5	SV 8.5 - 8	<b>0720 173 51</b>	10
-	12	10	40 (+/-1)	11 max.	3.5	SV 8.5 - 8	<b>0720 173 1</b>	10
-	12	15	41 (+/-1)	15.5 max.	3.5	SV 8.5 - 8	<b>0720 174 1</b>	10
-	12	18	41 (+/-1)	15.5 max.	3.5	SV 8.5 - 8	<b>0720 175 1</b>	10
C21W	12	21	41 (+/-1)	15.5 max.	3.5	SV 8.5 - 8	<b>0720 176 1</b>	10

12 volt

12/24 volt

HID bulb