






## CABLE CONNECTOR, NON-INSULATED

### AMP Micro Timer Contact / Flat Plug 1.6

Plug-in connector systems, 1.6 mm, with symmetrical locking lugs (except Art. no. 0558 190 90, 0558 190 91),

\* for single-wire seals

Mapping	mm <sup>2</sup>	Insulation dia. mm	Seal dia. mm	Plug mm	Material	Surface	Art. no.	PU/Qty.	
	0.2 - 0.5	Max. 1.6	-	1.6 x 0.6	CuSn	Sn (galvanised)	<b>0558 190 90</b>	100	
	0.5 - 1.0	Max. 2.0					<b>0558 190 91</b>		
	0.2 - 0.5	1.15 - 1.6	2.60		CuFe		<b>0558 190 92</b>		
	0.5 - 1.0	1.4 - 2.1					<b>0558 190 13</b>		
	0.2 - 0.5	1.15 - 1.6	-		CuSn		Sn (galvanised) gold-plated		<b>0558 190 20*</b>
	0.5 - 1.0	1.4 - 2.1							<b>0558 190 9</b>
	0.2 - 0.5	1.15 - 1.6	2.60		CuFe		Sn (galvanised)		<b>0558 190 93</b>
	0.5 - 1.0	1.4 - 2.1							<b>0558 190 14</b>
	0.5 - 1.0	1.4 - 2.1	-		CuSn		Sn (galvanised) gold-plated		<b>0558 190 21*</b>
									<b>0558 190 10</b>

Can be stored in ORSY® system

#### Additional recommended products:

Release tool Art. no. 0558 190 90, 0558 190 91

Release tool

Single wire seals

**Art. no. 0713 558 201**

**Art. no. 0713 558 311**

**Art. no. 0558 991 403**