

CABLE CONNECTOR, NON-INSULATED

AMPMODU and ELO Socket Contact/Pin Contact with locking lug						
Appearance	in mm ²	Pin dia. in mm	Material	Surface	Art. No.	P. Qty.
	0.35 - 0.5	0.63	various	Sn (tinned)	0558 190 4	100
					0558 171 001	
					0558 171 101	
					0558 171 002	
				Sn (tinned) gold-plated	0558 171 003	50
					0558 171 103	

Storable in [®]ORSY

Additional products - recommended:

Releasing tool **Art. No. 0713 558 201**

LEAR MKR/MKS PLUS Contact Plug-in connector systems, 1.5 mm dia., with symmetrical locking lugs, * for single-wire seals								
Appearance	in mm ²	Insul. dia. mm:	Seal dia. in mm	Pin dia. in mm	Material	Surface	Art. No.	P. Qty.
	0.5 - 1.0	1.4 - 2.3	3.40	1.50	CuSn	Sn (tinned)	0558 194 001*	50
	0.75 - 1.5	1.6 - 2.4	2.90				0558 194 002*	
	1.5 - 2.5	2.1 - 3.1	3.40				0558 194 003*	
	0.5 - 1.0	1.4 - 2.1	3.40				0558 194 101*	
	0.75 - 1.5	1.7 - 2.4	2.90				0558 194 102*	
	1.5 - 2.5	2.2 - 3.0	3.40				0558 194 103*	

Storable in [®]ORSY

Additional products - recommended:

Releasing tool **Art. No. 0713 558 510**

Individual wire seals **Art. No. 0558 991 4..**

LEAR VKR/VKS PLUS Contact Plug-in connector systems, 2.5 mm dia., with symmetrical locking lugs, * for single-wire seals								
Appearance	in mm ²	Insul. dia. mm:	Seal dia. in mm	Pin dia. in mm	Material	Surface	Art. No.	P. Qty.
	0.5 - 1.0	1.4 - 2.0	4.25	2.50	CuSn	Sn (tinned)	0558 195 001*	50
	1.5 - 2.5	2.0 - 2.9					0558 195 002*	
	0.5 - 1.0	1.4 - 2.1	3.40				0558 195 101*	
	1.5 - 2.5	2.2 - 3.0					0558 195 102*	

Storable in [®]ORSY

Additional products - recommended:

Releasing tool for VKR PLUS, Art. No. 0588 195 0..

Releasing tool for VKR PLUS, Art. No. 0588 195 1..

Individual wire seals

Art. No. 0713 558 520

Art. No. 0713 558 150

Art. No. 0558 991 4..