

## MINI SILVER FLAT PLUG-IN FUSE



Silver-plated version for improved heat removal

OEM quality

Proof of performance

ISO 8820-3

| Max. amperage | Color       | Max. nominal voltage | Min./max. operating temperature | Surface of contacts | Art. No.            | P. Qty. |
|---------------|-------------|----------------------|---------------------------------|---------------------|---------------------|---------|
| 2 A           | Gray        | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 02</b>  | 25      |
| 2 A           | Gray        | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 3 A           | Purple      | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 03</b>  | 25      |
| 3 A           | Purple      | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 4 A           | Pink        | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 04</b>  | 25      |
| 4 A           | Pink        | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 5 A           | Brown       | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 05</b>  | 25      |
| 5 A           | Brown       | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 7.5 A         | Ocher brown | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 075</b> | 25      |
| 7.5 A         | Ocher brown | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 10 A          | Red         | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 10</b>  | 25      |
| 10 A          | Red         | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 15 A          | Turquoise   | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 15</b>  | 25      |
| 15 A          | Turquoise   | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 20 A          | Yellow      | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 20</b>  | 25      |
| 20 A          | Yellow      | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 25 A          | White       | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 25</b>  | 25      |
| 25 A          | White       | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |
| 30 A          | Green       | 32 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 300 30</b>  | 25      |
| 30 A          | Green       | 32 V/DC              | -40 - 125 °C                    | Silver-plated       |                     | 100     |

Suitable for ORSY storage

## MINI-FLP SILVER FLAT PLUG-IN FUSE



### Note

3 A and 4 A versions feature tin-plated plug-in contacts

Silver-plated version for improved heat removal

OEM quality

| Max. amperage | Color       | Max. nominal voltage | Min./max. operating temperature | Surface of contacts | Art. No.           | P. Qty. |
|---------------|-------------|----------------------|---------------------------------|---------------------|--------------------|---------|
| 2 A           | Gray        | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 02</b> | 10      |
| 3 A           | Purple      | 58 V/DC              | -40 - 125 °C                    | Tin-plated          | <b>0731 302 03</b> | 10      |
| 4 A           | Pink        | 58 V/DC              | -40 - 125 °C                    | Tin-plated          | <b>0731 302 04</b> | 10      |
| 5 A           | Brown       | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 05</b> | 10      |
| 7.5 A         | Ocher brown | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 07</b> | 10      |
| 10 A          | Red         | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 10</b> | 10      |
| 15 A          | Turquoise   | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 15</b> | 10      |
| 20 A          | Yellow      | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 20</b> | 10      |
| 25 A          | White       | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 25</b> | 10      |
| 30 A          | Green       | 58 V/DC              | -40 - 125 °C                    | Silver-plated       | <b>0731 302 30</b> | 10      |

Suitable for ORSY storage