

FLAT PUSH-IN FUSE MICRO 2 SILVER



Silver-plated version for improved heat removal

OEM quality

Max. amperage	Color	Max. nominal voltage	Min./max. operating temperature	Surface of contacts	Art. No.	P. Qty.
5 A	Brown	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 05	10
7.5 A	Ocher brown	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 075	10
10 A	Red	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 10	10
15 A	Turquoise	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 15	10
20 A	Yellow	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 20	10
25 A	White	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 25	10
30 A	Green	32 V/DC	-40 to 125 °C	Silver-plated	0731 313 30	10

Suitable for ORSY storage

FLAT PUSH-IN FUSE MICRO 3 SILVER



Silver-plated version for improved heat removal

OEM quality

Max. amperage	Color	Max. nominal voltage	Min./max. operating temperature	Surface of contacts	Art. No.	P. Qty.
5 A	Brown	32 V/DC	-40 to 125 °C	Silver-plated	0731 315 05	10
7.5 A	Ocher brown	32 V/DC	-40 to 125 °C	Silver-plated	0731 315 075	10
10 A	Red	32 V/DC	-40 to 125 °C	Silver-plated	0731 315 10	10
15 A	Turquoise	32 V/DC	-40 to 125 °C	Silver-plated	0731 315 15	10

Suitable for ORSY storage