

FLRY VEHICLE CABLES



- As per DIN/ISO 6722
- PVC outer sheathing
- Rated voltage: $U_n = 50\text{ V}$, $U_{-} = 60\text{ V}$
- Temperature range: Class A, -40 °C to $+85\text{ °C}$
- Silicone-, cadmium- and lead-free

Delivery form: On plastic spools for ORSY® 10 dispenser system

Nominal cross-section in mm ²	0.35		0.5		0.75		1.0		1.5		2.5		4.0	
Approx. outer dia. in mm	1.25		1.50		1.80		2.00		2.30		2.90		3.50	
ID color	Art. No.	P. in m	Art. No.	P. in m	Art. No.	P. in m	Art. No.	P. in m	Art. No.	P. in m	Art. No.	P. in m	Art. No.	P. in m
Black	0770 035	100	0770 050	100	0770 075	100	0770 10	100	0770 100	100	0770 105	50	0770 110	50
Red	0770 035 1	100	0770 050 1	100	0770 075 1	100	0770 090 1	100	0770 101	100	0770 106	50	0770 110 0	50
Blue	0770 035 2	100	0770 050 2	100	0770 075 2	100	0770 090 2	100	0770 102	100	0770 107	50	-	-
Yellow	0770 035 3	100	0770 050 3	100	0770 075 3	100	0770 090 3	100	0770 103	100	0770 108	50	0770 110 00	50
Green	0770 035 4	100	0770 050 4	100	0770 075 4	100	0770 090 4	100	0770 104	100	0770 109	50	-	-
Gray	0770 035 5	100	0770 050 5	100	0770 075 41	100	0770 091 1	100	0770 104 1	100	0770 109 1	50	-	-
White	0770 035 42	100	0770 050 42	100	0770 075 42	100	0770 091 0	100	0770 104 2	100	0770 109 2	50	-	-
Brown	0770 035 9	100	0770 050 9	100	0770 075 9	100	0770 090 9	100	0770 104 0	100	0770 109 9	50	0770 110 9	50
Purple	0770 035 7	100	0770 050 7	100	0770 075 43	100	0770 090 7	100	0770 102 0	100	0770 107 0	50	-	-
Black/red	0770 035 55	100	0770 050 55	100	0770 075 49	100	0770 090 55	100	0770 104 55	100	-	-	-	-
Black/yellow	0770 035 65	100	0770 050 65	100	0770 075 93	100	0770 090 65	100	0770 104 65	100	-	-	-	-
Black/green	-	-	-	-	0770 075 50	100	0770 090 56	100	0770 104 56	100	-	-	-	-
Black/white	0770 035 54	100	0770 050 54	100	0770 075 48	100	0770 090 54	100	0770 104 54	100	-	-	-	-
Red/blue	-	-	-	-	0770 075 91	100	0770 090 91	100	0770 104 91	100	-	-	-	-
Red/yellow	0770 035 51	100	0770 050 51	100	0770 075 45	100	0770 090 51	100	0770 104 51	100	-	-	-	-
Red/gray	-	-	-	-	0770 075 70	100	0770 090 70	100	0770 104 70	100	-	-	-	-
Red/white	0770 035 69	100	0770 050 69	100	0770 075 69	100	0770 090 69	100	0770 104 69	100	-	-	-	-
Blue/black	-	-	-	-	0770 075 61	100	0770 091 2	100	0770 104 61	100	-	-	-	-
Blue/red	0770 035 60	100	0770 050 60	100	0770 075 60	100	0770 090 60	100	0770 104 60	100	-	-	-	-
Blue/green	-	-	-	-	0770 075 94	100	0770 090 59	100	0770 104 59	100	-	-	-	-
Blue/white	0770 035 58	100	0770 050 58	100	0770 075 58	100	0770 090 58	100	0770 104 58	100	-	-	-	-
Yellow/blue	-	-	-	-	0770 075 571	100	0770 090 571	100	0770 104 571	100	-	-	-	-
Yellow/green	0770 035 57	100	0770 050 57	100	0770 075 51	100	0770 091 6	100	0770 104 57	100	-	-	-	-
Green/red	-	-	-	-	0770 075 72	100	0770 090 72	100	0770 104 72	100	-	-	-	-
Green/yellow	0770 035 73	100	0770 050 73	100	0770 075 5	100	0770 090 5	100	0770 104 73	100	0770 109 90	50	-	-
Gray/black	-	-	-	-	0770 075 47	100	0770 091 3	100	0770 104 53	100	-	-	-	-
Gray/red	0770 035 52	100	0770 050 52	100	0770 075 46	100	0770 091 4	100	0770 104 52	100	-	-	-	-
Gray/green	-	-	-	-	0770 075 95	100	0770 091 5	100	0770 104 71	100	-	-	-	-
White/red	0770 035 573	100	0770 050 573	100	0770 075 573	100	0770 090 573	100	0770 104 573	100	0770 109 92	50	-	-
Brown/white	-	-	-	-	0770 075 92	100	0770 090 76	100	0770 104 76	100	-	-	-	-
Purple/black	-	-	-	-	0770 075 62	100	0770 090 62	100	0770 104 62	100	-	-	-	-

Delivery form: Bundled (type FLY)

- Temperature range: -40 °C to $+70\text{ °C}$

Nominal cross-section in mm ²	Outer dia. approx. in mm	Art. No. Black	Art. No. Red	Art. No. Brown	Art. No. Blue	P. in m
6.0	4.7	0770 111	0770 111 0	0770 111 9	0770 111 00	25
10.0	6.3	0770 111 2	0770 111 21	0770 111 22	-	50
16.0	7.3	0770 111 3	0770 111 301	-	-	50
25.0	9.1	0770 112	0770 112 301	-	-	25
35.0	11.0	0770 113	0770 113 301	-	-	25
50.0	12.6	0770 113 5	0770 113 501	-	-	25
70.0	14.8	0770 113 7	0770 113 701	-	-	25