

15-POLE SOCKET STANDARD 24 V



Including 15 crimp contacts
(12 x 1.5 mm², 3 x 2.5 mm²)

Art. No.	0510 950 251	0510 950 252
P. Qty.	1	1
Suitable for cable diameter	7-15 mm	7-15 mm
Contact design	Crimp contact	Crimp contact
Design	Straight screw connection	90° screw connection
Contact material	Copper alloy	Copper alloy
ISO	12098 Road vehicles - Connectors for the electrical connection of towing and towed vehicles - 15-pole connector for vehicles with 24 V nominal supply voltage	12098 Road vehicles - Connectors for the electrical connection of towing and towed vehicles - 15-pole connector for vehicles with 24 V nominal supply voltage

Applications

Installation on towing vehicles and trailers or semi-trailers.

Note

Two different rubber seals for flexible sheathed cables up to Ø 15 mm or corrugated tube DN 13 included

15-POLE CONNECTOR STANDARD 24 V



With strain relief

Including 15 crimp contacts
(12 x 1.5 mm², 3 x 2.5 mm²)

Art. No.	0510 950 205
P. Qty.	1
Suitable for cable diameter	16 mm
Contact design	Crimp contact
Design	Flared cap
Contact material	Copper alloy
ISO	12098 Road vehicles - Connectors for the electrical connection of towing and towed vehicles - 15-pole connector for vehicles with 24 V nominal supply voltage

Supplement to Art. No.:	Designation	Art. No.
0510 950 205	15-pin socket, standard 24 V	0510 950 251 0510 950 252
	Wire end ferrule without plastic sleeve	0557 175 928 0557 184 191
	Crimping pliers	0714 107 100
	Wire stripping pliers	0714 108 10
	FLRYY 111 Y Flexible sheathed cable	0770 118 015
	Contact spray	0890 100
	Silicone spray grease	0893 223

Application

For connecting sockets on towing vehicles to sockets on trailers or semi-trailers