

ABS/EBS SOCKET STANDARD 24 V



Art. No.	0510 950 161
P. Qty.	1
Suitable for cable diameter	7-15 mm
Contact design	Crimp contact
Design	Screw connection
Contact material	Copper alloy
ISO	7638 Road vehicles - Connectors for anti-lock braking systems

For braking systems

Including 7 crimp contacts
(5 x 1.5 mm², 2 x 6.0 mm²)

Applications

Installation on towing vehicles and trailers or semi-trailers.

Suitable for towing vehicles, trailers and semi-trailers with ABS (Anti-Lock Braking System) or EBS (Electronic Braking System).

Note

Two different rubber seals for flexible sheathed cables up to Ø 15 mm or corrugated tube DN 13 included

ABS/EBS CONNECTOR STANDARD 24 V



Art. No.	0510 950 115
P. Qty.	1
Suitable for cable diameter	16 mm
Contact design	Crimp contact
Design	Flared cap
Contact material	Copper alloy
ISO	7638 Road vehicles - Connectors for anti-lock braking systems

For braking systems

With strain relief

Including 7 crimp contacts
(5 x 1.5 mm², 2 x 6.0 mm²)

Application

For connecting sockets on towing vehicle to sockets on trailers or semi-trailers

Suitable for towing vehicles, trailers and semi-trailers with ABS (Anti-Lock Braking System) or EBS (Electronic Braking System).

Supplement to Art. No.:	Designation	Art. No.
0510 950 115	ABS/EBS socket, standard 24 V	0510 950 161
	Wire end ferrule without plastic sleeve	0557 175 928
		0557 184 191
		0557 184 218
	Crimping pliers	0714 107 100
	Wire stripping pliers	0714 108 10
	FLRYY 111 Y Flexible sheathed cable	0770 118 007
	Contact spray	0890 100
Silicone spray grease	0893 223	