

SPIRAL CABLES FOR 24 V BRAKE SYSTEMS

General data:

- Connection of socket outlets on pulling vehicle to socket outlets on trailer or semi-trailer
- ADR approval
- Approved by the German Technical Supervisory Society (TÜV).
- Complies with ISO 7638.
- Fabricated complete with plug



EBS Spiral Cables

- For use with EBS connections, 7-pole
- Wire cross-sections: 5 x 1.5 mm², 2 x 2.5 mm²

Fig.	Plug	Spiral diameter		Material	Max. working length	Art. No.	P. Qty.
1	2 x EBS 7-pole, 24 V	Large	Approx. 100 mm	Polyamide (PA)	4,500 mm	0510 950 70	1
2	2 x EBS 7-pole, 24 V	Small	Approx. 60 mm	Polyurethane (PU)	4,000 mm	0510 950 71	1



ABS Spiral Cables

- For use with ABS connections, 5-pole
- Wire cross-sections: 3 x 1.5 mm², 2 x 2.5 mm²

Fig.	Plug	Spiral diameter		Material	Max. working length	Art. No.	P. Qty.
1	2 x ABS 5-pole, 24 V	Large	Approx. 100 mm	Polyamide (PA)	4,500 mm	0510 950 50	1
2	2 x ABS 5-pole, 24 V	Small	Approx. 60 mm	Polyurethane (PU)	4,000 mm	0510 950 51	1



Practical addition: Parking socket

- Installation dimensions identical to those for ABS, EBS and 15-pole socket outlets
- For "storing" spiral plugs when one end is not required.

Suitable for	Art. No.	P. Qty.
ABS, EBS, 15-pole and 13-pole plug	0510 950 305	1