

Test Box 12 V

General data:

- Testing of trailer plugs and trailer car sockets with one device.
- Also suitable for vehicles with CAN-Bus.
- In accordance with ISO 1724, ISO 11446, ISO 3732.



Combi test box

Art. No. 0555 772 123

P. Qty. 1

Technical data:

- Operating voltage: 12 Volt DC / 3 Volt DC
- Holding-wire current: 0.2 mA
- Operating temperature: +5°C to +40°C
- Housing material: Plastic ABS

Functions:

- Testing of 7- and 13-pole sockets on the vehicle:
 - The test box simulates the trailer.
 - Function control: LED (9(-) and 10(-)) have to glow.
 - Test box is equipped with 4.5 m cable, hence one person can conduct the test.
- Testing of 7- and 13-pole plugs on the trailer:
 - The test box simulates the trailer car using battery operation (3-V button cell).
 - While testing 7-pole plugs the enclosed adaptor must be used.
- Overload protection
 - LED in the centre of the test box displays, whether the test can be performed or whether there is overload.

Delivery scope:

- Test box with 4.5 m cable and combi plug.
- Short adaptor for testing 7-pole trailer plugs.
- Lithium button cell 3 V CR 2032.
- Supplied in the practical storage case.



Spare button cell
Art. Nr. 0827 082 032