

# 13-pole System 12 V

## General data:

- According to ISO 11446 (with bayonet catch system).
- Operating temperature: -40°C to +85°C.
- Amperage: max. 25 A (with 2.5-mm<sup>2</sup>-cable).
- Contact identification according to ISO 11446.
- Screw contacts resist greater tensile loadings.



## 13 pin sockets

- Connection on the towcar.
- With shut down contact for fog tail lamp.
- Delivery includes rubber seal.
- Protection class IP 54.

Model	Contact type	Material contacts	Art. No.	P. Qty.
Plastic	Screw contacts	Copper-zinc-leg, nickel-plated	<b>0555 313 1</b>	2



## Rubber Base for Electrical Outlets

Application	Cable duct	Cable duct dia.	Art. No.	P. Qty.
13-pole sockets	Centre	6.5/9.5 mm	<b>0555 281 062</b>	5



## 13 pin connector

- Connection on the trailer.
- Screwing with rubber seal provides protection against splash water and dirt.
- Screwing is suitable for 9.0 mm to 11.5 mm diameter cable.

Model	Contact type	Material contacts	Art. No.	P. Qty.
Plastic	Screw contacts	Copper-zinc leg, nickel-plated	<b>0555 313 0</b>	2



### Connection accessories:

13 core vehicle cables 13 x 1.5 mm <sup>2</sup>	<b>Art. No. 0770 124</b>	Contact care Silicone spray grease	<b>Art. No. 0893 223</b>
Wire Stripping Pliers	<b>Art. No. 0714 108 10</b>	Contact spray	<b>Art. No. 0890 100</b>
Wire End Ferrules 1.5 mm <sup>2</sup>	<b>Art. No. 0557 175 928</b>	Contact size	<b>Art. No. 0893 65</b>
2.5 mm <sup>2</sup>	<b>Art. No. 0557 184 191</b>	Contact OL	<b>Art. No. 0893 60</b>
Crimping pliers	<b>Art. No. 0714 107 100</b>	Contact OS	<b>Art. No. 0893 61</b>
		Contact SL	<b>Art. No. 0893 70</b>