

STARTER BATTERY DURACELL® STARTER

Reliable and high-quality

Art. No.	0511 101 001	0511 101 002	0511 101 012	0511 101 003	0511 101 004	0511 101 005
P. Qty.	1	1	1	1	1	1
Supplier product designation	DS 44	DS 45	DS 45 H	DS 45 L	DS 55	DS 60
ETN number	544 109 036	545 077 030	545 059 040	545 079 030	555 119 045	560 409 048
Housing type	LB1	E2	L1	E2	LB2	LB2
Rechargeable battery/ battery capacity	44 Ah	45 Ah	45 Ah	45 Ah	55 Ah	60 Ah
Cold test current/EN	360 A	300 A	400 A	300 A	450 A	480 A
Cold test current/SAE	400 A	320 A	420 A	320 A	480 A	500 A
Length	210 mm	218 mm	210 mm	218 mm	241 mm	241 mm
Width	175 mm	135 mm	175 mm	135 mm	175 mm	175 mm
Crate height	175 mm	203 mm	190 mm	203 mm	175 mm	175 mm
Height	175 mm	225 mm	190 mm	225 mm	175 mm	175 mm
Switching	0	0	0	1	0	0
Battery design	mGGA	0 - not applicable	mGGA	0 - not applicable	mGGA	mGGA
Floor strip	B13	B01	B13	B01	B13	B13
Terminal	1	1	1	1	1	1
Product weight (per item)	11.5 kg	13 kg	12.000 kg	13 kg	13.5 kg	14.5 kg
Nominal voltage	12 V/DC	12 V/DC	12 V/DC	12 V/DC	12 V/DC	12 V/DC

Art. No.	0511 101 006	0511 101 007	0511 101 008	0511 101 009	0511 101 010	0511 101 011
P. Qty.	1	1	1	1	1	1
Supplier product designation	DS 62	DS 70	DS 72	DS 72 L	DS 88	DS 95
ETN number	562 019 051	570 144 064	572 012 066	572 033 066	588 120 066	595 033 072
Housing type	L2	LB3	L3	L3	LB5	L5
Rechargeable battery/ battery capacity	62 Ah	70 Ah	72 Ah	72 Ah	88 Ah	95 Ah
Cold test current/EN	510 A	640 A	660 A	660 A	660 A	720 A
Cold test current/SAE	540 A	680 A	700 A	700 A	700 A	760 A
Length	241 mm	278 mm	278 mm	278 mm	354 mm	354 mm
Width	175 mm	175 mm	175 mm	175 mm	175 mm	175 mm
Crate height	190 mm	175 mm	190 mm	190 mm	175 mm	190 mm
Height	190 mm	175 mm	190 mm	190 mm	175 mm	190 mm
Switching	0	0	0	1	0	0
Battery design	mGGA	mGGA	mGGA	mGGA	mGGA	mGGA
Floor strip	B13	B13	B13	B01	B13	B13
Terminal	1	1	1	1	1	1
Product weight (per item)	15 kg	17 kg	18 kg	18 kg	20.5 kg	22.5 kg
Nominal voltage	12 V/DC	12 V/DC	12 V/DC	12 V/DC	12 V/DC	12 V/DC