

## CHARGING CLAMPS



### Partially insulated – 100 A

- Galvanized sheet steel, PVC plastic handles
- Max. load: 100 A
- Total length: 143 mm
- Weight: 65 g
- Opening angle: 35°/29 mm

Color	Art. No.	P. Qty.
Red	<b>0773 321 1</b>	1
Black	<b>0773 321 6</b>	1



### Partially insulated – 120 A

- Galvanized sheet steel, PVC plastic handles
- Max. load: 120 A
- Total length: 180 mm
- Weight: 97 g
- Opening angle: 50°/50 mm

Color	Art. No.	P. Qty.
Red	<b>0773 314 1</b>	1
Black	<b>0773 314 6</b>	1



### Fully insulated – 200 A

- Galvanized sheet steel; the conductive side is reinforced with a galvanized brass insert
- Cold-resistant insulation (Escorena Ultra EVA)
- Cable connection up to 35 mm<sup>2</sup>, with cable-pinching lug:
  - M6 bolt and self-locking nut
  - Strain relief
- Max. load: 200 A
- Length: 160 mm
- Weight: approx. 160 g
- Opening angle: 45°/35 mm

Color	Art. No.	P. Qty.
Red	<b>0773 306 1</b>	1
Black	<b>0773 306 6</b>	1



### Fully insulated – 600 A

- Galvanized sheet steel; with copper-mesh strip terminal connection. Each clamp side is reinforced by a galvanized brass insert.
- Cold-resistant insulation (Escorena Ultra EVA)
- Cable connection up to 35 mm<sup>2</sup>, with cable-pinching lug:
  - M6 bolt and self-locking nut
  - Strain relief
- Max. load: 600 A
- Length: 160 mm
- Weight: approx. 230 g
- Opening angle: 45°/35 mm

Color	Art. No.	P. Qty.
Red	<b>0773 305 11</b>	1
Black	<b>0773 305 61</b>	1