



### Starter Cable 25 mm<sup>2</sup>

- With two startsafe boxes (protected against overvoltage, no polarity protection).
- For petrol engines up to 5,500 cm<sup>3</sup> and diesel engines up to 3,000 cm<sup>3</sup>.
- Cable cross-section: 25 mm<sup>2</sup>.
- Cable length: 3,5 m.
- Weight: 2,7 kg.
- Fully insulated plastic clamps for loads up to 350 A.
- Compliant with DIN.
- Comes in a rugged cloth bag.

**Art. No. 0772 025 350**

P. Qty. 1



### Starter Cable 35 mm<sup>2</sup>

- With two startsafe boxes in armoured plastic housing (protected against overvoltage, no polarity protection).
- For petrol engines up to 7,000 cm<sup>3</sup> and diesel engines up to 4,000 cm<sup>3</sup>.
- Cable cross-section: 35 mm<sup>2</sup>.
- Cable length: 4,5 m.
- Weight: 4,7 kg.
- Fully insulated sheet steel clamps for loads up to 600 A.
- Compliant with DIN.
- Comes in a rugged, tear-resistant cloth bag.

**Art. No. 0772 035 521**

P. Qty. 1



### Truck-Start Starter Cable 50 mm<sup>2</sup>

- With two startsafe boxes in armoured plastic housing (protected against overvoltage, no polarity protection).
- For all lorry engines.
- Highly flexible individual cables (guided in parallel through connectors); the cables even remain flexible at temperatures below freezing.
- Cable cross-section: 50 mm<sup>2</sup>.
- Cable length: 5 m.
- Weight: 7,0 kg.
- Fully insulated 1,000 A fully cast angled clamps – clamps are tapered at the end.
- Comes in a rugged, tear-resistant cloth bag.

**Art. No. 0772 035 520**

P. Qty. 1



### Starter Cable 35 mm<sup>2</sup>

- For petrol engines up to 7,000 cm<sup>3</sup> and diesel engines up to 4,000 cm<sup>3</sup>.
- Cable cross-section: 35 mm<sup>2</sup>.
- Cable length: 4,5 m.
- Weight: 4,7 kg.
- Max. load: 600 A.
- Clamps:
  - galvanised sheet steel,
  - both sides of clamps are reinforced via a galvanised brass insert,
  - with copper mesh tape pole connection,
  - Escorene Ultra EVA insulation.
- Compliant with DIN.
- Comes in a rugged, tear-resistant cloth bag.

**Art. No. 0772 035 450**

P. Qty. 1