

AUTOMATIC JUMPSTART UNIT



For all vehicles with 12 V on-board power systems and vehicles up to 4,000 cm³ with 24 V on-board power systems.

- For mobile, battery-operated jump-starting of cars and utility vehicles with 12 V and 24 V on-board voltage systems.
- Automatic start function.
→ Starting power not summoned until needed, which means greater starting power.
- Automatic protection against polarity switching.
- Automatic voltage selection between 12 V and 24 V (manual voltage selection also possible).
- Fully insulated, solid angled clamps with highly flexible solid-rubber lines.
- De-energized connection and disconnection of clamps to vehicle on-board power system.
- Protection against voltage peaks.
- Overload protection when starting up.
- Battery status indication via LEDs.
- Short-circuit-proof (protection of internal battery via high-current fuse).

Technical data:	
Operating voltage	12 V/24 V DC
Starting current	For 12 V: 1,400 A, for 24 V: 600 A
Peak current	For 12 V: 4,200 A, for 24 V: 1,400 A
Internal battery	2 x 16 Ah = 32 Ah
Cable diameter	50 mm ²
Cable length	120 cm
Weight	18 kg
Dimensions (H x W x D):	430 x 200 x 230 mm

Art. No. 0772 122 42

P. Qty. 1