

## SEMI-AUTOMATIC STARTER UNIT



Technical Data:	Art. No. 0772 121	Art. No. 0772 122
Operating voltage	12 V DC	12 V DC
Starting current intensity	600A	1.200 A
Peak current	1.500 A	3.100 A
Internal battery	1 x 16 Ah	2 x 16 Ah = 32 Ah
Cable diameter	35 mm <sup>2</sup>	35 mm <sup>2</sup>
Cable length	120 cm	120 cm
Weight	10 kg	18 kg
Dimensions (L x W x H)	430 x 200 x 230 mm	430 x 200 x 230 mm

**For gasoline and Diesel engines up to 2,200 cm<sup>3</sup> capacity.**

- Mobile starting assistance for cars with 12 V wiring system.
- Reverse polarity indication with LED lamps and separate On/Off lever (semi-automatic).
- Protection against voltage peaks.
- Protection against short circuits / overload.
- Fully insulated, angled solid clips with highly flexible heavy-duty rubber cables.
- De-energized clipping and unclipping on the vehicle's wiring system.
- Battery charge indicated by LED lamps.

**Art. No. 0772 121**

P. Qty. 1

**For all vehicles with 12 V wiring system.**

- Not suitable for US trucks.
- Mobile starting assistance for cars with 12 V wiring system.
- Reverse polarity indication with LED lamps and separate On/Off lever (semi-automatic).
- Protection against voltage peaks.
- Protection against short circuits / overload.
- Fully insulated, angled solid clips with highly flexible heavy-duty rubber cables.
- De-energized clipping and unclipping on the vehicle's wiring system.
- Battery charge indicated by LED lamps.

**Art. No. 0772 122**

P. Qty. 1