

# Metal Valves for Passenger Cars



Rim hole (mm)	L (mm)	Size (mm)	Art. No.	P. Qty.
Special passenger car sports rims	42	14	<b>0879 563</b>	10/100
Universal with PA disk		11	<b>0879 563 1</b>	
Universal with PA disk (import)		11	<b>0879 563 10</b>	100

## Brass Valve

- Version: Brass, nickel-plated.
- Suitable for all common light-metal wheels with 11.3 mm rim valve hole.
- Recom. tightening torque: 4-6 Nm.
- Rim thickness: 1.8-4.0 mm.



Version	L (mm)	Size (mm)	Art. No.	P. Qty.
Universal with PA disk	42	11	<b>0879 563 2</b>	10
Universal with PA disk black anodized*			<b>0879 563 25</b>	

\* Corrosion protection layer through electrolytic oxidation of aluminum → Improved resistance to scratching.

## Aluminum Valve

- Version: Aluminum alloy.
- 65% weight reduction compared to ordinary metal valves.
- Improved material compatibility for aluminum wheels.
- Suitable for all common light-metal wheels with 11.3 mm rim valve hole.
- Recom. tightening torque: 3-5 Nm.
- Rim thickness: 1.8-4.0 mm.



Extended by mm	Alligator Comp. No.	Art. No.	P. Qty.
13	33.0251	<b>0879 70</b>	20
19	33.0301	<b>0879 71</b>	

## Valve Extension Caps

- For passenger cars.