

# ZINC PUNCH BALANCE WEIGHT FOR CAR STEEL RIMS

With innovative geometry for easier and quicker fitting



## Type 133 ZL

**Universal use on almost all steel rims**

thanks to mounting groove

**Unambiguous visual differentiation**

possible from balance weights for car aluminum rims

Weight of balance weight	Material	Surface	Color	Comparison number	Art. No.	P.
5 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 05</b>	100
10 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 10</b>	100
15 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 15</b>	100
20 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 20</b>	100
25 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 25</b>	100
30 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 30</b>	100
35 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 35</b>	50
40 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 40</b>	50
45 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 45</b>	50
50 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 50</b>	50
55 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 55</b>	50
60 g	ZN    Zinc	ZFSLH    Zinc flake, coating thickness 5-8, silver, sealed; N. WIS-LV003	Silver	Franken 80-Z, Hofmann 160, 161, 164	<b>083086 60</b>	50

Suitable for ORSY storage

Designation	Art. No.
Balance weight pliers	<b>0695391885</b>
Mechanic's Glove	<b>0899400529</b>
	<b>0899400530</b>
	<b>0899400531</b>
	<b>0899400532</b>

## Instructions

Before fitting, select the corresponding weight according to the rim shape.

When doing this, take account of the different rim types and rim flanges.

## Note

A maximum of two powerful strikes should be used for fitting. Increasing the number of strikes can damage the coating of the weights.