

Tools for Installing Eyes

① Wad Punch

- Forged steel.
- For punching rubber, cardboard, leather, plastic tarpaulins etc.

② Driving Punch

- Processable material thickness: 1.4 – 2.1 mm.
- Average tarpaulin thickness for comm. veh. = 0.7 mm.




For eye type	Dimensions	Wad punch Art. No.	P. Qty.	Driving punch Art. No.	P. Qty.
Round eyes	Dia. 4 mm	0880 223 204	1	–	–
	Dia. 5 mm	0880 223 205	1	–	–
	Dia. 6 mm	0880 223 206	1	–	–
	Dia. 8 mm	0880 223 208	1	–	–
	Dia. 10 mm	0880 227 3	1	0880 227 2	1
	Dia. 11 mm	0880 223 211	1	–	–
	Dia. 12 mm	0880 228 3	1	0880 228 2	1
	Dia. 14 mm	0880 223 214	1	–	–
	Dia. 16 mm	0880 230 3	1	0880 230 2	1
	Dia. 18 mm	0880 223 218	1	–	–
	Dia. 20 mm	0880 232 201	1	0880 232 202	1
	Dia. 25 mm	0880 233 251	1	0880 233 252	1
Oval eyes	Dia. 36 mm	0880 823 61	1	0880 823 62	1
	Dia. 40 mm	0880 236 401	1	0880 236 402	1
	17 x 11	0880 203 11	1	0880 203 12	1
	22.5 x 13.5	0880 202 11	1	0880 202 12	1
	42 x 22	0880 221 11	1	0880 221 12	1
	60 x 21	–	–	–	–

Clasps

Stirrup clasps

- All clasps have a hole diameter of 5 mm.


for round eyes 36 mm dia., 40 mm dia. and oval eyes 42 x 22 mm



	Model	Material	Dimensions					Art. No.	P. Qty.
			H in mm	b in mm	L in mm	B in mm	A in mm		
	Straight base plate	Galvanised steel	21	21	71	20	51	0880 830	25
			30	21	71	20	51	0880 831	50
			25	21	71	20	51	0880 832	
			38	21	71	20	51	0880 833	
			45	21	71	20	51	0880 835	25
	Octagonal base plate	Galvanised steel	30	20	65	40	51	0880 801	50
			25	20	65	40	51	0880 802	25
			38	20	65	40	51	0880 803	

for round eyes 40 mm dia. and oval eyes 42 x 22 mm

	Model	Material	Dimensions					Art. No.	P. Qty.
			H in mm	b in mm	L in mm	B in mm	A in mm		
	Curved hoop	Galvanised steel	30	28	76	15	55	0880 799	25



for round eyes 40 mm dia. and oval eyes 42 x 22 mm

	Model	Material	Dimensions					Art. No.	P. Qty.
			H in mm	b in mm	L in mm	B in mm	A in mm		
	For folding over as per customs regulations	Galvanised steel	37	20	72	22	51	0880 814 37	25
			45	20	72	22	51	0880 814 45	
			55	20	72	22	51	0880 814 55	
	with welded-on counterplate	Galvanised steel	37	20	45	21	28	0880 813 37	25
			45	20	45	21	28	0880 813 45	
			55	20	55	21	28	0880 813 55	