

Workshop Package:



Spoiler windshield wipers

P. Qty.: 10 x windshield wipers with profile edge protection including preinstalled multi-adapters and 9 x 3 U-clip adapter for high market coverage.

Designation:	Length in mm	Art. No.	P. Qty.
Spoiler windshield wipers	450	0848 160 450	10
	475	0848 160 475	
	500	0848 160 500	
	525	0848 160 525	
	550	0848 160 550	
	575	0848 160 575	
	600	0848 160 600	
	625	0848 160 625	
	650	0848 160 650	
Standard windshield wipers	280	0848 170 280	10
	300	0848 170 300	
	325	0848 170 325	
	350	0848 170 350	
	380	0848 170 380	
	400	0848 170 400	
	425	0848 170 425	
	450	0848 170 450	
	475	0848 170 475	
	500	0848 170 500	
	525	0848 170 525	
	550	0848 170 550	
	575	0848 170 575	
600	0848 170 600		
625	0848 170 625		
650	0848 170 650		
700	0848 170 700		

Passenger-Car Windshield Wipers

Passenger-car standard and spoiler wipers

Art. No. 0848 160 ... (Spoiler)

Art. No. 0848 170 ... (Standard)

Practical workshop package

- Low stocking costs
- Lean assortment
- High market coverage due to individual equipping of vehicles

Profile edge protection

- Protects graphite coating of rubber profile in package.

Natural rubber wiping lip with graphite coating

- Extremely smooth-running
- UV and ozone-resistant
- High operating temperature range

Premounted multi-adapter

- For fast and easy mounting with a high market coverage of common hook wiper arms.

Metal bar system with stainless-steel rivets

- Highly resistant to the effects of weathering (360 hrs. in salt spray test according to DIN EN ISO 9227).

Stainless-steel pin joints on plastic mounts

- Enable smooth running of wiper blade with long service life.

Aerodynamic design

- Spoiler wiper blade: Plastic aerodynamic spoiler; enables a 5-10 mph (10-20 kph) higher speed before wiper blade lifts off. The spoiler provides for clear vision in heavy driving and oncoming winds.

Easy to refill

- We recommend the refills from our assortment, Art. No. 0848 106 10 or 0848 147 50.

Notes

Installation:

For aerodynamic reasons (spoiler function), it must be ensured during mounting that the punched logo on the wiper blade faces toward the engine hood.

Safety:

Make sure that the windshield is free of oil, wax, tar and other soiling so that the service life is not reduced.

The windshield wipers should be replaced in case of smearing or decreasing wiping performance.

We recommend replacing the windshield wipers every 6 months.

Tip:

Always lay a protective material on the windshield when mounting!



Adapter overview

Premounted multi-adapter



9x3 U-clip

