

### 45° Pipe Connector



- For connection to cutting-ring fittings.

da	h	l	Size	Art. No.	P. Qty.
6	35 mm	25 mm	10	<b>0884 600 058</b>	10

### 45° Pipe Connector with groove

- For connection to insertion fittings.

da	h	l	Size	Art. No.	P. Qty.
6	35 mm	25 mm	10	<b>0884 600 059</b>	10



### Straight Pipe Connector

- For connection to cutting-ring fittings.

da	L	Size	Art. No.	P. Qty.
6	20 mm	10	<b>0884 600 054</b>	10
6	30 mm	10	<b>0884 600 051</b>	

### Straight Pipe Connector with groove


- For connection to insertion fittings.

da	L	Size	Art. No.	P. Qty.
6	20 mm	10	<b>0884 600 055</b>	10

## Plastic Hose Lines

### Plastic Tube, semi-rigid

- For central grease lubrication units: For use as a secondary line between the main manifold and the divider manifold or between the divider manifold and the lubrication point.
- Pursuant to DIN 73378.
- With size 6 x 1.5, an insertion sleeve is not necessary.




da	s	di	Designation	Art. No.	P. Qty./m
6	1.5 mm	3.0 mm	6x1.5*	<b>0884 600 009</b>	25
6	1.5 mm	3.0 mm	6x1.5**	<b>0884 600 004</b>	100
6	1.5 mm	3.0 mm	6x1.5 empty	<b>0884 600 003</b>	25

\* Filled with NLGI Class 2 grease

\*\* Filled with NLGI Class 000 low-viscosity grease

### Plastic Tube, flexible

- For central low-viscosity grease lubrication units: Can be used as a lubrication point line between re-greasing manifold and lubrication point.
- Pursuant to DIN 73378.
- Must be used with Insertion Sleeve Art. No. 0884 604 603.



da	s	di	Designation	Art. No.	P. Qty./m
4	0.85 mm	2.3 mm	4x0.85**	<b>0884 600 005</b>	50

\*\* filled with NLGI Class 000 low-viscosity grease

**Utility Vehicle Low-Viscosity Grease,  
25-kg container  
Art. No. 0893 881 4**