

AIR-CONDITIONER LEAK-DETECTION ADDITIVE



Content	Art. No.	Quantity
Press-Out Tool	0891 764 010	1
Filling Adapter	0764 000 114	1
A/C Leak-Detection Additive	0892 764 010	6

Instructions:

See application overview of leak-detection additive or the work instructions enclosed with the product.

Applications:

Can be used as a preventive measure for localizing leaks in R134a and R1234yf air-conditioning systems. Can also be used in systems with an electrical compressor.

Leak-detection assortment for mobile use with R134a and R1234yf air-conditioning systems.

Can be used without an air-conditioner service unit

Can be used on the go.

One use per system is all that's needed

High proportion of fluorescent substances

Very good material compatibility

- O-rings and seals are not attacked
- Additive can remain in the air-conditioning circuit after use

Fulfills the SAE J2297 provision for R 134a, PAG oil and ester oil

Compatible with PAG oil

Art. No. 0964 764 025

P. Qty. 1

Additional articles:

LED UV Leak-Detection Flashlight
Art. No. 0964 764 095, P. Qty. 1

Leak-Detection Additive Remover
Art. No. 0892 764 401, P. Qty. 1/12

This information is only a recommendation based on our experience. Preliminary testing required!
When using the product, both the technical data sheet and the specifications of the applicable regulations are to be complied with.