

SOLDERED CABLE LUGS

DIN 46211

- Material: brass, tinned.



Cross-section in mm ²	Flange hole	Cable entry in mm	Material thickness approx. in mm	Length x width approx. in mm	Art. No.	P. Qty.
6.0 - 16.0	M6	6.0 x 4.3	1.20	26.5 x 11.0	0557 921 9	25/100
6.0 - 16.0	M8	8.0 x 4.3	1.20	31.5 x 15.0	0557 922 0	25/100
6.0 - 16.0	M10	10.0 x 4.3	1.20	35.5 x 19.0	0557 922 1	25/100
10.0 - 25.0	M6	6.0 x 5.4	1.50	29.4 x 11.0	0557 922 3*	25/100
10.0 - 25.0	M8	8.0 x 5.4	1.50	34.4 x 15.0	0557 922 4	25/100
10.0 - 25.0	M10	10.0 x 5.4	1.50	38.4 x 19.0	0557 922 5	25/100
16.0 - 35.0	M6	6.0 x 6.8	1.80	33.5 x 13.0	0557 922 7*	25/100
16.0 - 35.0	M8	8.0 x 6.8	1.80	37.5 x 15.0	0557 922 8	25/100
16.0 - 35.0	M10	10.0 x 6.8	1.80	41.5 x 19.0	0557 922 9	25/100
16.0 - 35.0	M12	12.0 x 6.8	1.80	46.0 x 22.0	0557 923 0	10/25
25.0 - 50.0	M8	8.0 x 8.2	2.00	40.5 x 15.0	0557 922 81*	25/100
25.0 - 50.0	M10	10.0 x 8.2	2.00	44.5 x 19.0	0557 923 3	10/25
25.0 - 50.0	M12	12.0 x 8.2	2.00	49.0 x 22.0	0557 923 4	10/25
35.0 - 70.0	M8	8.0 x 9.5	2.50	44.4 x 17.0	0557 923 6*	25/100
35.0 - 70.0	M10	10.0 x 9.5	2.50	47.4 x 19.0	0557 923 7	10/25
35.0 - 70.0	M12	12.0 x 9.5	2.50	51.8 x 22.0	0557 923 8	10/25
50.0 - 95.0	M10	10.0 x 11.2	3.00	54.5 x 21.0	0557 924 0	5/25
50.0 - 95.0	M12	12.0 x 11.2	3.00	58.0 x 22.0	0557 924 1	5/25
70.0 - 120.0	M10	10.0 x 13.5	3.50	54.5 x 21.0	0557 924 3	5/25
70.0 - 120.0	M12	12.0 x 13.5	3.50	58.0 x 22.0	0557 924 4	5/25

* = Not included in assortment Art. No. 0964 557 5.

ORSY® storable

Assortment



Art. No. 0964 557 5
P. Qty. 1

Contents: 16 sizes = 72 pieces

Additional products



Art. No. 0984 990 100
P. Qty. 1

WGLG 100
Self-Igniting Gas Soldering Unit



Art. No. 0987 1...

Soft Solders