

MIG/MAG Shielding-Gas Welding Torch

MB 25 AK

Air-cooled, with Bikox hose package and central connector KZ-2

Ideal for all apparatus, vehicle, machine and steel construction

- Optimal handling thanks to ergonomically designed handle system.
- Original Bikox hose package is highly flexible, compact, rugged and has a long service life.
- Hose packages have central connection system, also called "Euro connection".



Euro connection

Designation	Art. No.	P. Qty.
MIG/MAG Hose Package, complete, 3 m long	0984 260 130	1
MIG/MAG Hose Package, complete, 4 m long	0984 260 140	
Handle Section with Push-Button, complete	0984 160 260	
Push-Button, Ergo-Handle	0984 160 265	
Torch Neck	0984 260 17	
Nozzle Block	0984 260 18	2
Contact Tip, 0.8 mm dia.	0984 260 108	5
Contact Tip, 1.0 mm dia.	0984 260 112	
Contact Tip, 1.2 mm dia.	0984 260 110	
Contact Tip for Aluminium Wire, 0.8 mm dia.	0984 260 115	
Contact Tip for Aluminium Wire, 1.0 mm dia.	0984 260 116	
Contact Tip for Aluminium Wire, 1.2 mm dia.	0984 260 117	3
Gas Nozzle, conical	0984 260 14	
Gas Nozzle, cylindrical	0984 260 16	
Spot Gas Nozzle	0984 260 15	2
Retaining spring	0984 260 13	5

Technical data

according to EN 60 974-9

Load: 230 A CO₂
200 A Mixed gas M 21
according to EN 439
60% ED

Suitable wire dia.: 0.8 – 1.2 mm

The individual parts of the MB25 also fit in models of the same design; use the dimensioned drawings as a comparison.

Delivered state of the hose package with contact tip, dia. 1.2 mm.

PTFE Cores for Aluminium Welding Wire
Art. No. 0984 300 05

PTFE Cores for Stainl.-Steel Welding Wire
Art. No. 0984 300 06
0984 300 07