

MIG/MAG Shielding-Gas Welding Torch

MB 15 AK

Air-cooled, with Bikox hose package and KZ-2 Central Connector

Ideal for all equipment, vehicle, machine and steel construction

- Optimal handling thanks to ergonomically designed handle system.
- Original Bikox hose package is highly flexible, compact, rugged and has a long service life.
- Hose packages have the central connection system, also called "Euro connection".



Euro connection

Designation	Art. No.	P. Qty.
MIG/MAG Hose Package, complete, 3 m long	0984 160 130	1
MIG/MAG Hose Package, complete, 4 m long	0984 160 140	
Handle Section with push-button, complete	0984 160 260	
Push-Button, Ergo-Handle	0984 160 265	
Torch Neck	0984 160 17	
Gas Nozzle Carrier	0984 160 18	2
Contact Tip, 0.6 mm dia.	0984 160 106	5
Contact Tip, 0.8 mm dia.	0984 160 108	
Contact Tip, 1.0 mm dia.	0984 160 110	
Contact Tip for Aluminum Wire, 0.8 mm dia.	0984 160 115	
Contact Tip for Aluminum Wire, 1.0 mm dia.	0984 160 116	
Gas Nozzle, conical	0984 160 14	3
Gas Nozzle, cylindrical	0984 160 16	
Spot Gas Nozzle	0984 160 15	2
Retaining Spring	0984 160 13	5

Technical data as per EN 60974-9

Load: 180 A CO₂
150 A mixed gas M 21
as per EN 439
60% ED

**Suitable
wire dia.:** 0.6 – 1.0 mm

The individual parts of the MB 15 also fit in models of the same design; use the dimensioned drawings as a comparison.

Hose package supplied with 1.0 mm-dia. contact tip.

**PTFE Cores for Aluminum
Welding Wire
Art. No. 0984 300 05**
**PTFE Cores for Stainless-Steel
Welding Wire
Art. No. 0984 300 06**