

LACQUER SPRAYS

in all solid colors

Durable nitroalkydal quality at a high technical level.

High quality nitroalkydal.

- Quick drying.
- High gloss.
- Good distribution.

Can be painted over all known primers, filler products, and paint types.

Wide range of uses, e.g.

- Commercial vehicles,
- Bodywork,
- Radiators,
- Window frames,
- Steel constructions, etc.

Method for use:

- Shake the can well for about 3 minutes before use.
- The application surface must be clean, dry, and grease-free.
- Remove rust and old loose paint, sand and prime
- Spraying distance: 20-25 cm.
- Maintain a flash-off time of approx. 5 min between spray coats.
- Storage temperature + 15 °C to + 25 °C and up to 60% rel. humidity.
- Optimum working temperature + 20 °C.

Technical features:

Quick-drying paint resin

Does not contain heavy metals

Drying time at 20 °C

Dust-dry < 10 min

Non-sticky < 20 min

Touch proof < 60 min

Paint Spray	Content in ml.	Art. No.	P. Qty.
Satin finish	400	0893 330	12
Silk matt	400	0893 331	12
Dull matt	400	0893 332	12
High-gloss	400	0893 333	12

Additional products:

Silicon remover

Art. No. 0893 222

0893 222 5

0893 222 600

Primer, e.g. Art. No. 0893210 1

Breathing protection mask, Art. No. 0899 160



Spraymaster



The practical attachment for your spray can

Art. No. 0891 090

P./Qty. 1

Important: Orders larger than 12 cans in high gloss, silk matt, or dull matt.

Note:

Always state the color and color number in the text relating to the items.

Delivery time: 3 days after order date.