according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ACTIVE FOAM EXTRA STRONG - 200 L

Product code : 0893045200

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Cleansing agents, alkaline., Detergent

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: prodsafe@wuerth.com

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Category 1A H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

Precautionary statements : Prevention:

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P330 + P331 + P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 + P310 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER/doctor. P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER/doctor.

Storage:

P405 Store locked up.

Hazardous components which must be listed on the label:

Potassium hydroxide

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1-Propanaminium, 3-amino-N-	61789-40-0	Eye Dam. 1; H318	>= 4 - < 10
(carboxymethyl)-N,N-dimethyl-, N-	263-058-8	Aquatic Chronic 3;	
coco acyl derivs., hydroxides,		H412	
inner salts			
Isotridecanol, ethoxylated	69011-36-5	Acute Tox. 4; H302	>= 1 - < 3
		Eye Dam. 1; H318	
2-Butoxyethanol	111-76-2	Acute Tox. 4; H302	>= 1 - < 10
	203-905-0	Acute Tox. 4; H332	
	603-014-00-0	Acute Tox. 4; H312	
		Skin Irrit. 2; H315	
		Eye Irrit. 2; H319	
Potassium hydroxide	1310-58-3	Met. Corr. 1; H290	>= 1 - < 2
	215-181-3	Acute Tox. 4; H302	
	019-002-00-8	Skin Corr. 1A; H314	
		Eye Dam. 1; H318	
Quaternary coco alkyl methyl	863679-20-3	Acute Tox. 4; H302	>= 1 - < 3

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

amine ethoxylate methyl chloride Skin Irrit. 2; H315
Eye Dam. 1; H318

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention immediately. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control centre immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes digestive tract burns.

Causes serious eye damage.

Causes severe burns.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

Metal oxides

Chlorine compounds Oxides of phosphorus

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe vapours or spray mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

practice

Keep container tightly closed.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Store locked up. Keep tightly closed. Store in accordance with the particular national

regulations.

Advice on common storage : Do not store with the following product types:

Strong oxidizing agents
Organic peroxides

Explosives

Storage class (TRGS 510) : 8A, Combustible, corrosive hazardous materials

Recommended storage tem- : > 0 °C

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

perature

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-Butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m3	2000/39/EC
Further information	Identifies the	possibility of significa	ant uptake through the skin, I	ndicative
		STEL	50 ppm 246 mg/m3	2000/39/EC
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	10 ppm 49 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Commission for dangerous substances, Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-Butoxyethanol	111-76-2	butoxy acetic acid: 100 mg/l (Urine)	In case of long- term exposure: after more than one shift	TRGS 903
		butoxy acetic acid: 200 mg/l (Urine)	In case of long- term exposure: after more than one shift	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
tetrasodium N,N- bis(carboxylatomethyl)-L-glutamate	Workers	Inhalation	Long-term systemic effects	7,3 mg/m3
	Workers	Skin contact	Long-term systemic effects	15000 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1,8 mg/m3
	Consumers	Skin contact	Long-term systemic effects	7500 mg/kg bw/day

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

	Consumers	Ingestion	Long-term systemic effects	1,5 mg/kg bw/day
1-Propanaminium, 3- amino-N- (carboxymethyl)-N,N- dimethyl-, N-coco acyl derivs., hydroxides, inner salts	Workers	Inhalation	Long-term systemic effects	44 mg/m3
	Workers	Skin contact	Long-term systemic effects	12,5 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	7,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	7,5 mg/kg bw/day
Sodium Tripolyphos- phate	Workers	Inhalation	Long-term systemic effects	0,661 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	0,661 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,375 mg/kg bw/day
	Workers	Skin contact	Acute systemic ef- fects	0,375 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,661 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	0,66 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,375 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	0,375 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,75 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	0,75 mg/kg bw/day
2-Butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m3
	Workers	Inhalation	Acute systemic ef- fects	663 mg/m3
	Workers	Inhalation	Acute local effects	246 mg/m3
	Workers	Skin contact	Long-term systemic effects	75 mg/kg bw/day
	Workers	Skin contact	Acute systemic ef- fects	89 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	49 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	426 mg/m3
	Consumers	Inhalation	Acute local effects	123 mg/m3
	Consumers	Skin contact	Long-term systemic effects	38 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	44,5 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic	3,2 mg/kg

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

			effects	bw/day
	Consumers	Ingestion	Acute systemic ef- fects	13,4 mg/kg bw/day
Potassium hydroxide	Workers	Inhalation	Long-term local effects	1 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	1 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
tetrasodium N,N-	Oral (Secondary Poisoning)	67 mg/kg food
bis(carboxylatomethyl)-L-		
glutamate		
1-Propanaminium, 3-amino-N-	Fresh water	0,0135 mg/l
(carboxymethyl)-N,N-dimethyl-,		
N-coco acyl derivs., hydroxides,		
inner salts		
	Marine water	0,00135 mg/l
	Sewage treatment plant	3000 mg/l
	Marine water	0,1 mg/kg
	Fresh water	1 mg/kg
	Soil	0,8 mg/kg
Sodium Tripolyphosphate	Fresh water	0,005 mg/l
	Marine water	0,005 mg/l
	Intermittent use/release	0,05 mg/l
	Fresh water sediment	0,19 mg/kg
	Soil	0,14 mg/kg
2-Butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Intermittent use/release	9,1 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	3,13 mg/kg
	Oral (Secondary Poisoning)	0,02 mg/kg food

8.2 Exposure controls

Engineering measures

Minimize workplace exposure concentrations.

Use with local exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn. If splashes are likely to occur, wear:

Face-shield

Hand protection

Material : Nitrile rubber
Break through time : 240 min
Glove thickness : > 0,5 mm

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : characteristic

Odour Threshold : No data available

pH : 13 (20 °C)

concentrate

Melting point/freezing point : No data available

Initial boiling point and boiling

range

100 °C

Flash point : 350 °C

Other information: No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 23 hPa (20 °C)

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

Relative vapour density : No data available

Density : 1,08 g/cm3 (20 °C)

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

Acids

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of:

exposure

Inhalation Skin contact Ingestion

Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Acute oral toxicity : LD50 (Rat): 2.335 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Isotridecanol, ethoxylated:

Acute oral toxicity : LD50 (Rat): > 500 - 2.000 mg/kg

Remarks: Based on data from similar materials

2-Butoxyethanol:

Acute oral toxicity : LD50 (Rat): 1.746 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg

Method: Expert judgement

Potassium hydroxide:

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

Acute oral toxicity : LD50 (Rat): 365 mg/kg

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Acute oral toxicity : LD50 (Rat): > 300 - 2.000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Isotridecanol, ethoxylated:

Species: Rabbit

Result: No skin irritation

2-Butoxyethanol:

Species: Rabbit

Method: Directive 67/548/EEC, Annex V, B.4.

Result: Skin irritation

Potassium hydroxide:

Result: Corrosive after 3 minutes or less of exposure

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Result: Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Species: Rabbit

Method: OECD Test Guideline 405 Result: Irreversible effects on the eye

Isotridecanol, ethoxylated:

Species: Rabbit

Result: Irreversible effects on the eye

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

2-Butoxyethanol:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritation to eyes, reversing within 21 days

Potassium hydroxide:

Species: Rabbit

Result: Irreversible effects on the eye

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

2-Butoxyethanol:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Potassium hydroxide:

Exposure routes: Skin contact

Species: Guinea pig Result: negative

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Result: negative

Germ cell mutagenicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydrox-

ides, inner salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: Directive 67/548/EEC, Annex, B.13/14

Result: negative

Remarks: Based on data from similar materials

: Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on data from similar materials

2-Butoxyethanol:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Method: OECD Test Guideline 474

Result: negative

Potassium hydroxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Genotoxicity in vitro : Test Type: Ames test

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

2-Butoxyethanol:

Species: Mouse

Application Route: inhalation (vapour)

Exposure time: 106 weeks

Method: OECD Test Guideline 451

Result: negative

Reproductive toxicity

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion
Method: OECD Test Guideline 414

Result: negative

2-Butoxyethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Mouse

Application Route: Ingestion

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rabbit

Application Route: inhalation (vapour) Method: OECD Test Guideline 414

Result: negative

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Species: Rat NOAEL: 300 mg/kg

Application Route: Ingestion Exposure time: 90 Days

Method: OECD Test Guideline 408

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,1 mg/l

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 6,5 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 14,7 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 2,1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC0 (Pseudomonas putida): 3.000 mg/l

Exposure time: 16 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic tox-

icity)

NOEC: 0,135 mg/l

Exposure time: 37 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 0,932 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Isotridecanol, ethoxylated:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1 - 10 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 : > 1 - 10 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 : > 1 - 10 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

2-Butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.464 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.800 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840

mg/l

Exposure time: 72 h

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 3.3 23.05.2017 675192-00004 Date of first issue: 11.06.2010

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 286

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC: > 100 mg/l Exposure time: 21 d

Species: Danio rerio (zebra fish) Method: OECD Test Guideline 204

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC: 100 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Toxicity to fish : LC50 :> 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 : > 1 - 10 mg/l

Exposure time: 72 h

12.2 Persistence and degradability

Components:

1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-coco acyl derivs., hydroxides, inner salts:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 91,6 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Isotridecanol, ethoxylated:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90 % Exposure time: 28 d

2-Butoxyethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 90,4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Quaternary coco alkyl methyl amine ethoxylate methyl chloride:

Biodegradability : Result: Readily biodegradable.

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

Biodegradation: 60 % Exposure time: 28 d

Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

2-Butoxyethanol:

Partition coefficient: n-

octanol/water

log Pow: 0,81

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

200129, detergents containing dangerous substances

unused product

200129, detergents containing dangerous substances

uncleaned packagings

150110, packaging containing residues of or contaminated by

dangerous substances

SECTION 14: Transport information

14.1 UN number

ADN : UN 1814

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Revision Date: SDS Number: Date of last issue: 14.03.2017 23.05.2017 675192-00004 Date of first issue: 11.06.2010 3.3

ADR UN 1814 RID UN 1814 **IMDG UN 1814 IATA** UN 1814

14.2 UN proper shipping name

ADN POTASSIUM HYDROXIDE SOLUTION **ADR** POTASSIUM HYDROXIDE SOLUTION **RID** POTASSIUM HYDROXIDE SOLUTION **IMDG** POTASSIUM HYDROXIDE SOLUTION

Potassium hydroxide solution **IATA**

14.3 Transport hazard class(es)

ADN 8 **ADR** 8 RID 8 **IMDG** 8 **IATA** 8

14.4 Packing group

ADN

Packing group Ш Classification Code C5 Hazard Identification Number : 80 Labels 8

ADR

Ш Packing group Classification Code C5 Hazard Identification Number : 80 Labels 8 Tunnel restriction code (E)

RID

Ш Packing group Classification Code C5 Hazard Identification Number : 80 Labels 8

IMDG

Packing group Ш Labels 8 **EmS Code**

F-A, S-B

IATA (Cargo)

Packing instruction (cargo

aircraft)

Packing instruction (LQ) Y840 Packing group Ш

855

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

Version Date of last issue: 14.03.2017 Revision Date: SDS Number: 675192-00004 Date of first issue: 11.06.2010 3.3 23.05.2017

Labels Corrosive

IATA (Passenger)

Packing instruction (passen-851

ger aircraft)

Packing instruction (LQ) Y840 Packing group Ш

Labels Corrosive

14.5 Environmental hazards

ADN

Environmentally hazardous no

ADR

Environmentally hazardous no

RID

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

Not applicable

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class

WGK 2 water endangering

Classification according VwVwS, Annex 4. (Germany)

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 2,3 %, 24,8 g/l

Remarks: VOC content excluding water

Regulation (EC) No. : less than 5 %: Phosphates, Cationic surfactants, Amphoteric

648/2004, as amended surfactants, Non-ionic surfactants

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H290 : May be corrosive to metals. H302 : Harmful if swallowed. H312 : Harmful in contact with skin.

H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H318 : Causes serious eye damage. H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Chronic : Chronic aquatic toxicity Eye Dam. : Serious eye damage

Eye Irrit. : Eye irritation

Met. Corr. : Corrosive to metals
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

TRGS 903 : TRGS 903 - Biological limit values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regula-

according to Regulation (EC) No. 1907/2006



ACTIVE FOAM EXTRA STRONG - 200 L

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 14.03.2017

 3.3
 23.05.2017
 675192-00004
 Date of first issue: 11.06.2010

tion; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture:

Classification procedure:

Skin Corr. 1A H314 Based on product data or assessment Eye Dam. 1 H318 Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN