

## P10 FAST GRINDING POLISH PLUS



### Pad recommendation:

"Blue" or "Lambskin" polishing pad

### Use:

Shake bottle well before using. Moisten the surface of the selected polishing pad evenly with the paste and apply a small quantity on the surface to be polished. Lay the polishing pad evenly on the

Contents in kg	Art. No.	P. Qty.
1	<b>0893 150 010</b>	1/5

area and start the machine. Polish the area with a certain pressure until grinding traces or paint imperfections have been removed. Remove residual polish with a microfiber cloth. Remove any remaining streaks with P30 Anti-Hologram Polish Plus.

**Highly abrasive high-gloss polish for quickly removal of surface defects in fresh repair and hardened top-coat paints.**

**Innovative powdered property of aluminum oxide.**

- Extremely high surface removal rate and unmatched gloss level.
- Sanding grooves **can be effortlessly removed from a grain of P1500.**

**Thick consistency.**

- No spraying of the polish.
- Efficient in consumption.
- Minimal dust creation.
- No laborious recleaning of adjacent areas.

**Can be applied manually and by machine. For conventional and scratchproof paint types.**

**Suitable for use on used and new paint surfaces.**

**Silicone-free.**

## P20 HIGH-GLOSS POLISH PLUS



### Pad recommendation:

"Blue" or "Lambskin" polishing pad

### Use:

Shake bottle well before using. Moisten the surface of the selected polishing pad evenly with the paste and apply a small quantity on the surface to be polished. Lay the polishing pad evenly on the area

Contents in kg	Art. No.	P. Qty.
1	<b>0893 150 020</b>	1/5
5	<b>0893 150 025</b>	1

and start the machine. Polish the area with a certain pressure until grinding traces or paint imperfections have been removed. Remove residual polish with a microfiber cloth. Remove any remaining streaks with P30 Anti-Hologram Polish Plus.

**Medium-abrasive high-gloss polish for efficient paint care.**

**Specially matched powdered property of aluminum oxide.**

- Moderate surface removal rate and extremely high gloss level.
- Sanding grooves **can be effortlessly removed from a grain of P2000.**

**Thick consistency.**

- No spraying of the polish.
- Efficient in consumption.
- Minimal dust creation.
- No laborious recleaning of adjacent areas.

**Can be applied manually and by machine. For conventional and scratchproof paint types.**

**Suitable for use on used and new paint surfaces.**

**Silicone-free.**

### Additional items:

**Microfiber Cloth**

**Art. No. 0899 900 131** P. Qty. 3

**Polishing Sponges**

**Art. No. 0585 ...** P. Qty. 2

This information is only a recommendation based on our experience. Preliminary testing required! For further information, see the technical information leaflet and container layout.