

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : LIQUID METAL FE 1 - 500 G (comp. B)  
Product code : 0893449

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Adhesives and/or sealants, Dual-component adhesive

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau  
Telephone : +49 794015 0  
Telefax : +49 794015 10 00  
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

#### 1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

---

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2      H315: Causes skin irritation.  
Eye irritation, Category 2      H319: Causes serious eye irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :   
Signal word : Warning  
Hazard statements : H315 Causes skin irritation.  
H319 Causes serious eye irritation.

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

Precautionary statements : **Prevention:**  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### 2.3 Other hazards

None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,4,6-tris((Dimethylamino)methyl)phenol	90-72-2 202-013-9 603-069-00-0	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318	>= 1 - < 3

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

- || In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- || If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

- || Risks : Causes skin irritation.  
Causes serious eye irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
- 

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- || Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- || Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- || Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.
- || Hazardous combustion products : Carbon oxides  
Nitrogen oxides (NO<sub>x</sub>)  
Sulphur oxides

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2016
2.0	27.06.2017	1138457-00002	Date of first issue: 06.12.2016

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

#### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Avoid inhalation of vapour or mist.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice.  
Take care to prevent spills, waste and minimize release to the environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:  
Strong oxidizing agents

Storage class (TRGS 510) : 10, Combustible liquids

Storage period : 24 Months

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Iron silicide	Workers	Inhalation	Long-term local effects	0,3 mg/m <sup>3</sup>

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,4,6-tris{(Dimethylamino)methyl}phenol	Fresh water	0,084 mg/l
	Marine water	0,0084 mg/l
	Sewage treatment plant	0,2 mg/l
	Intermittent use/release	0,84 mg/l

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Hand protection  
Material : Nitrile rubber

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2016
2.0	27.06.2017	1138457-00002	Date of first issue: 06.12.2016

Break through time : > 480 min  
Glove thickness : > 0,4 mm  
Directive : DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : viscous

Colour : dark blue

Odour : mild

Odour Threshold : No data available

pH : 3 - 5 (20 °C)

Melting point/freezing point : No data available

Initial boiling point and boiling range : 204 °C

Flash point : > 200 °C  
Other information: Ignitable (see flash point)

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 1,15 g/cm<sup>3</sup> (25 °C)

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : > 257 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Particle size : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

##### Acute toxicity

|| Not classified based on available information.

##### Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

|| Acute oral toxicity : LD50 (Rat): 1.653 mg/kg

|| Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

##### Skin corrosion/irritation

|| Causes skin irritation.

##### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

|| Species: Rabbit

|| Method: OECD Test Guideline 404

|| Result: Corrosive after 1 to 4 hours of exposure

##### Serious eye damage/eye irritation

|| Causes serious eye irritation.

##### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

|| Species: Rabbit

|| Result: Irreversible effects on the eye

##### Respiratory or skin sensitisation

##### Skin sensitisation

|| Not classified based on available information.

##### Respiratory sensitisation

|| Not classified based on available information.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

### Components:

#### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: equivocal

Test Type: Buehler Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Result: negative

#### **Germ cell mutagenicity**

|| Not classified based on available information.

### Components:

#### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

#### **Carcinogenicity**

|| Not classified based on available information.

#### **Reproductive toxicity**

|| Not classified based on available information.

### Components:

#### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

#### **STOT - single exposure**

|| Not classified based on available information.

#### **STOT - repeated exposure**

|| Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

### Repeated dose toxicity

#### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Species: Rat  
NOAEL: 15 mg/kg  
Application Route: Ingestion  
Exposure time: 43 Days  
Method: OECD Test Guideline 422

#### Aspiration toxicity

|| Not classified based on available information.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 180 mg/l  
Exposure time: 96 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 84 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 6,25 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC : 2 mg/l  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.2 Persistence and degradability

#### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 4 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Components:

##### **2,4,6-tris{(Dimethylamino)methyl}phenol:**

Partition coefficient: n-octanol/water : log Pow: 0,219

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version 2.0      Revision Date: 27.06.2017      SDS Number: 1138457-00002      Date of last issue: 06.12.2016  
Date of first issue: 06.12.2016

---

### II

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

Not relevant

#### 12.6 Other adverse effects

No data available

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

- used product  
080411, adhesive and sealant sludges containing organic solvents or other dangerous substances
- unused product  
080411, adhesive and sealant sludges containing organic solvents or other dangerous substances
- uncleaned packagings  
150110, packaging containing residues of or contaminated by dangerous substances

Acc. Packaging Ordinance properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

---

### SECTION 14: Transport information

#### 14.1 UN number

Not regulated as a dangerous good

#### 14.2 UN proper shipping name

Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2016
2.0	27.06.2017	1138457-00002	Date of first issue: 06.12.2016

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

Water contaminating class (Germany) : WGK 2 water endangering  
Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 0 %

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

### Full text of H-Statements

H302 : Harmful if swallowed.  
H314 : Causes severe skin burns and eye damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2016
2.0	27.06.2017	1138457-00002	Date of first issue: 06.12.2016

H318 : Causes serious eye damage.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Eye Dam. : Serious eye damage  
Skin Corr. : Skin corrosion

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Skin Irrit. 2 H315  
Eye Irrit. 2 H319

### Classification procedure:

Calculation method  
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## LIQUID METAL FE 1 - 500 G (comp. B)

Version	Revision Date:	SDS Number:	Date of last issue: 06.12.2016
2.0	27.06.2017	1138457-00002	Date of first issue: 06.12.2016

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN