

LOCK CYLINDER SPRAY



Excellent creeping properties ensure very good moisture displacement.

Prevents freezing in winter, as no moisture can accumulate.

Contains corrosion protection additives.

Provides permanent protection of locking mechanisms.

Resin and acid-free.

Sensitive components are not attacked.

Silicone-free.

Designation	Content in ml	Art. No.	P. Qty.
Aerosol can	50	0893 052	12/24*

* in display carton

Applications:

For the care of all types of locks.

Use:

Insert capillary tube in lock and spray briefly.

Do not use together with powdered graphite.

MAINTENANCE SPRAY



Highly effective wear protection additives ensure excellent friction reduction.

Prevents premature wearing and seizing of hammer drills in machine holders.

Outstanding creeping and cleaning performance.

- Keeps door and window hinges running smoothly.
- Lubricates and protects all precision mechanical devices.

Resin and acid-free.

Sensitive components are not attacked.

Silicone-free.

Also suitable for use as gun oil.

Designation	Content in ml	Art. No.	P. Qty.
Aerosol can	150	0893 051	1/12
Pressure Spray	100	0893 051 702	1/24

Applications:

For lubricating hinges, tool and machine holders.

Use:

Spray the lubricating points to be treated.

Lubricant system

Oil Grease Paste Dry lubricant Corrosion protection

This information is only a recommendation based on our experience. Preliminary testing required.