

Socket Outlets and Plugs for Special Application

3-Pole System, 12 V

General data:

- In accordance with DIN 9680.
- Operating temperature: -25°C to $+75^{\circ}\text{C}$.
- Max. amperage: 25 A.
- Protection class: IP 54.
- Screw connection with rubber seal provides protection against splashed water and dirt.
- Application: Used with agricultural machines, tractors and refrigerated trucks.



3-Pole Socket

Version	Contact type	Contact material	Art. No.	P. Qty.
plastic	push-on contacts	copper-zinc alloy nickel-plated	0555 315 200	2



3-Pole Connector

Version	Contact type	Contact material	Art. No.	P. Qty.
plastic	push-on contacts	copper-zinc alloy nickel-plated	0555 315 100	2

2-Pole System, 6 V – 24 V

General data:

- In accordance with ISO 4165.



2-Pole Socket

- Operating temperature: -40°C to $+105^{\circ}\text{C}$.
- Amperage: max.: 16 A.
- Protection class: IP 67.
- 30 cm cable 2.5 mm² with extrusion-coated plastic housing.
- With screw-on cover.

Version	Contact type	Contact material	Art. No.	P. Qty.
plastic, incl. cable	–	–	0555 316 2	2



2-Pole Connector

- Amperage: max. 8 A.

Version	Contact type	Contact material	Art. No.	P. Qty.
plastic	push-on contacts	copper-zinc alloy nickel-plated	0555 316 1	2



Connection accessories:

Multi-wire vehicle lines	Contact care
2 x 1.5 mm ² Art. No. 0770 120	Silicone Spray
3 x 1.5 mm ² Art. No. 0770 116	Grease Art. No. 0893 223
Wire Stripping	Contact Spray Art. No. 0890 100
Pliers Art. No. 0714 108 10	Contact SW Art. No. 0893 65
Push-On Receptacles	Contact OL Art. No. 0893 60
4.8 x 0.8 Art. No. 0558 531 2	Contact OS Art. No. 0893 61
6.3 x 0.8 Art. No. 0558 991 7	Contact SL Art. No. 0893 70
Crimping Pliers Art. No. 0714 107 107	