

PRESPRAY



Designation	Contents in L	Art. No.	P. Qty.
Canister	25	0893 025 9	1

Areas of application:

Matched to the high-pressure cleaning / prewash in brush washing systems, the high-pressure gantry car washes, high-pressure washers in self-service car washes and on presprayer units.

Use:

Dose undiluted in the brush washing system.

User concentration: approx. 0.5-2%.

In high-pressure equipment/self-service car washes: Stir 1 part Prespray into 2 parts water.

In prespray units: Stir 1 part Prespray into 49 parts water.

Note:

Do not allow to dry on, and do not use on galvanized surfaces. Carry out preliminary tests on surfaces that are sensitive to alkalis, such as aluminum. Protect from frost.

Alkaline cleaning agent for the pre-treatment and removal of stubborn soiling

Effective precleaner

- Speeds up the softening and removal of stubborn soiling such as dead insects, tar, tree sap, bird droppings
- Improves the washing result

Multi-functional application

- Can be used for the high-pressure cleaning / prewash and in the presprayer unit

Free of phosphate, AOX and silicone.

pH value in the concentrate: approx. 13

Degrades easily in accordance with OECD* requirements. Does not hamper the effectiveness of light fluid separators.

* OECD = Organisation for Economic Co-operation and Development

Additional articles:

Active Wash
Art. No. 0893 025 1

Active Foam Wash
Art. No. 0893 025 2

Hot preserving wax
Art. No. 0893 025 3

Drying aid
Art. No. 0893 025 6