

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SUPER RTV SILICONE CLEAR - 200 ML

Product code : 08933314

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Sealant
stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG
Reinhold-Würth-Str. 12-17
74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person : prodsafe@wuerth.com
responsible for the SDS

1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version 2.8 Revision Date: 14.02.2017 SDS Number: 547674-00010 Date of last issue: 06.01.2017
Date of first issue: 04.03.2016

Precautionary statements :

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

2.3 Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-Pentanone, O,O',O''-(methylsilylidyne)trioxime	37859-55-5 484-460-1 01-2120004323-76	Acute Tox. 4; H302 Eye Irrit. 2; H319 STOT RE 2; H373	>= 1 - < 10
2-Pentanoneoxim	623-40-5 484-470-6	Acute Tox. 4; H302 Eye Irrit. 2; H319 STOT RE 2; H373	>= 1 - < 10
2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime	58190-62-8 01-2120006148-66	Acute Tox. 4; H302 Eye Irrit. 2; H319 STOT RE 2; H373	>= 1 - < 10
Dimethylbis[(1-oxodecyl)oxy]stannane	68928-76-7 273-028-6	Acute Tox. 4; H302 Repr. 2; H361d STOT RE 1; H372 Aquatic Chronic 3; H412	>= 0,1 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

- | | | |
|-------------------------|---|---|
| If inhaled | : | If inhaled, remove to fresh air.
Get medical attention. |
| In case of skin contact | : | In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse. |
| In case of eye contact | : | Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists. |
| If swallowed | : | If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water. |

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides
Silicon oxides
Nitrogen oxides (NO_x)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing method : Use extinguishing measures that are appropriate to local cir-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

ods

cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

- Local/Total ventilation : Use only with adequate ventilation.
Use only in an area equipped with explosion proof exhaust ventilation.
- Advice on safe handling : Avoid inhalation of vapour or mist.
Do not swallow.
Avoid contact with eyes.
Avoid prolonged or repeated contact with skin.
Handle in accordance with good industrial hygiene and safety practice.
Keep away from water.
Protect from moisture.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Do not spray on an open flame or other ignition source.
- Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight.
- Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
- Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
------------	---------	------------------	--------------------	-------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

**SUPER RTV SILICONE CLEAR - 200 ML**Version
2.8Revision Date:
14.02.2017SDS Number:
547674-00010Date of last issue: 06.01.2017
Date of first issue: 04.03.2016

		of exposure)		
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Pentanone, O,O',O''-(methylsilyldyne)trioxime	Workers	Inhalation	Long-term systemic effects	1,164 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,165 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,287 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,0825 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,085 mg/kg bw/day
2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime	Workers	Inhalation	Long-term systemic effects	1,198 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,17 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,29 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,085 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,085 mg/kg bw/day
2-Pentanone oxim	Workers	Inhalation	Long-term systemic effects	8,3 mg/m3
	Workers	Inhalation	Acute systemic effects	24,9 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,208 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	0,624 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	2,07 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version
2.8

Revision Date:
14.02.2017

SDS Number:
547674-00010

Date of last issue: 06.01.2017
Date of first issue: 04.03.2016

			effects	
	Consumers	Inhalation	Acute systemic effects	6,21 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,125 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0,375 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,125 mg/kg bw/day
	Consumers	Ingestion	Acute systemic effects	0,375 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-Pentanone, O,O',O''-(methylsilyldiyl)trioxime	Fresh water	0,1 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	2,15 mg/l
	Fresh water sediment	0,569 mg/kg
	Marine sediment	0,057 mg/kg
2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime	Soil	0,04422 mg/kg
	Fresh water	0,103 mg/l
	Marine water	0,01 mg/l
	Sewage treatment plant	2,22 mg/l
	Fresh water sediment	0,586 mg/kg
2-Pentanone oxim	Marine sediment	0,059 mg/kg
	Soil	0,046 mg/kg
	Fresh water	0,088 mg/l
	Marine water	0,0088 mg/l
	Intermittent use/release	0,88 mg/l
	Sewage treatment plant	2 mg/l
	Fresh water sediment	0,5 mg/kg
	Marine sediment	0,05 mg/kg
	Soil	0,05 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).

Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust ventilation.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses

Hand protection

Material : Latex gloves
Break through time : 480 min
Glove thickness : > 0,5 mm
Directive : DIN EN 374

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version 2.8	Revision Date: 14.02.2017	SDS Number: 547674-00010	Date of last issue: 06.01.2017 Date of first issue: 04.03.2016
----------------	------------------------------	-----------------------------	---

Material	: Chloroprene
Break through time	: 480 min
Glove thickness	: > 0,65 mm
Directive	: DIN EN 374

Material	: Nitrile rubber
Break through time	: 480 min
Glove thickness	: > 0,4 mm
Directive	: DIN EN 374

Material	: Fluorinated rubber
Break through time	: 480 min
Glove thickness	: > 0,7 mm
Directive	: DIN EN 374

Material	: butyl-rubber
Break through time	: 480 min
Glove thickness	: > 0,47 mm
Directive	: DIN EN 374

Remarks	: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.
---------	---

Skin and body protection	: Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential. Wear the following personal protective equipment: Flame retardant antistatic protective clothing. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
--------------------------	---

Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
------------------------	---

Filter type	: Self-contained breathing apparatus
-------------	--------------------------------------

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: paste
Propellant	: Propane, Butane
Colour	: transparent
Odour	: characteristic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	Not applicable
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	hydrolyses
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	Not applicable
Self-ignition	:	not auto-flammable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.
Vapours may form explosive mixture with air.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed upon contact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture
Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
Water

10.6 Hazardous decomposition products

Contact with water or humid air : 2-Pentanoneoxim
Methyl Isobutyl Ketoxime

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

2-Pentanone, O,O',O''-(methylsilyldiylne)trioxime:

Acute oral toxicity : LD50 (Rat): 1.234 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Method: OECD Test Guideline 425

Acute dermal toxicity : LD50 (Rat): > 1.782 mg/kg
Remarks: Based on data from similar materials

2-Pentanoneoxim:

Acute oral toxicity : LD50 (Rat): 1.133 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 1,22 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Acute oral toxicity : LD50 (Rat): > 1.000 - < 2.000 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: Directive 67/548/EEC, Annex V, B.3.
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Acute oral toxicity : LD50 (Rat): 894 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

2-Pentanone, O,O',O''-(methylsilyldiyl)trioxime:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Species: Rabbit
Result: No skin irritation

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2-Pentanone, O,O',O''-(methylsilylidyne)trioxime:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritation to eyes, reversing within 21 days

Remarks: Based on data from similar materials

2-Pentanoneoxim:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritation to eyes, reversing within 21 days

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Irritation to eyes, reversing within 21 days

Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

2-Pentanoneoxim:

Test Type: Buehler Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Test Type: Buehler Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Pentanone, O,O',O''-(methylsilyldiyl)trioxime:

- | | |
|------------------------------------|---|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative |
| | : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive |
| | : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative |
| Genotoxicity in vivo | : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative |
| Germ cell mutagenicity- Assessment | : Weight of evidence does not support classification as a germ cell mutagen. |

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

- | | |
|------------------------------------|---|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative |
| | : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: positive |
| | : Test Type: in vitro micronucleus test
Method: OECD Test Guideline 487
Result: negative |
| Genotoxicity in vivo | : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 475
Result: negative |
| Germ cell mutagenicity- Assessment | : Weight of evidence does not support classification as a germ cell mutagen. |

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

2-Pentanone, O,O',O''-(methylsilylidyne)trioxime:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

2-Pentanone oxim:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

STOT - repeated exposure

Not classified based on available information.

Components:

2-Pentanone, O,O',O''-(methylsilylidyne)trioxime:

Exposure routes: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Remarks: Based on data from similar materials

2-Pentanoneoxim:

Exposure routes: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

Exposure routes: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Exposure routes: Ingestion

Target Organs: Immune system, Central nervous system

Assessment: Shown to produce significant health effects in animals at concentrations of 10 mg/kg bw or less.

Repeated dose toxicity

Components:

2-Pentanone, O,O',O''-(methylsilylidyne)trioxime:

Species: Rat

LOAEL: > 10 - 100 mg/kg

Application Route: Ingestion

Exposure time: 90 Days

Remarks: Based on data from similar materials

2-Pentanoneoxim:

Species: Rat

NOAEL: 15 mg/kg

LOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 6 Weeks

Method: OECD Test Guideline 422

2-Pentanone, O,O',O''-(ethenylsilylidyne)trioxime:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Species: Rat
NOAEL: 34 - 41 mg/kg
Application Route: Ingestion
Exposure time: 90 Days
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Species: Rat
NOAEL: < 1,6 mg/kg
Application Route: Ingestion
Exposure time: 90 Days
Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-Pentanone, O,O',O''-(methylsilylidyne)trioxime:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to microorganisms	:	EC50 : > 21,5 mg/l Exposure time: 28 d

2-Pentanoneoxim:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue:
2.8	14.02.2017	547674-00010	06.01.2017
			Date of first issue: 04.03.2016

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 88 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 32 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : > 20 mg/l
Exposure time: 28 d

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 117 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 117 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 103 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 37 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC0 : > 22,2 mg/l
Exposure time: 28 h
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 17 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): 37 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

EC10 (Desmodesmus subspicatus (green algae)): 5,7 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

12.2 Persistence and degradability

Components:

2-Pentanone, O,O',O''-(methylsilyldiyl)trioxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Dimethylbis[(1-oxoneodecyl)oxy]stannane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3 %
Exposure time: 35 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

2-Pentanone, O,O',O''-(ethenylsilyldiyl)trioxime:

Partition coefficient: n-octanol/water : log Pow: 1,43

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

2-Pentanone, O,O',O''-(ethenylsilyldyne)trioxime:

Partition coefficient: n-octanol/water : log Pow: 1,25

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product
080409, waste adhesives and sealants containing organic solvents or other dangerous substances
160504, gases in pressure containers (including halons) containing dangerous substances

unused product
080409, waste adhesives and sealants containing organic solvents or other dangerous substances
160504, gases in pressure containers (including halons) containing dangerous substances

uncleaned packagings
150110, packaging containing residues of or contaminated by dangerous substances
150104, metallic packaging

Acc. Packaging Ordinance properly emptied packaging:
Properly emptied, non-contaminated packaging of non-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

hazardous products can be supplied to a system for the collection of sales packaging.

SECTION 14: Transport information

14.1 UN number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS
IATA	:	Aerosols, flammable

14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADN		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1

ADR		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

RID		
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Hazard Identification Number	:	23
Labels	:	2.1

IMDG		
Packing group	:	Not assigned by regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Dimethylbis[(1-oxodecyl)oxy]stannane (20)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Water contaminating class (Germany) : WGK 2 water endangering
Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 3,76 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H319	: Causes serious eye irritation.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure if swallowed.
H373	: May cause damage to organs through prolonged or repeated exposure.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Chronic aquatic toxicity
Eye Irrit.	: Eye irritation
Repr.	: Reproductive toxicity
STOT RE	: Specific target organ toxicity - repeated exposure
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



SUPER RTV SILICONE CLEAR - 200 ML

Version	Revision Date:	SDS Number:	Date of last issue: 06.01.2017
2.8	14.02.2017	547674-00010	Date of first issue: 04.03.2016

Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Aerosol 1

H222, H229

Classification procedure:

Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN