

CONTACT SPRAY ADHESIVE CLEANER



Adhesive remover for cleaning the contact spray adhesive system.

Great cleaning and loosening power.

- Efficient cleaning of hardened contact adhesive from the application system.
- Economical in use.

Does not leave grease behind.

- No lubricant film remains on the surface after mechanical cleaning.
- Cleaning is carried out with a dry, lint-free cloth only (no water).

Large container.

- Portable and handy in use.
- Efficient material provisioning.

Designation/Container	Contents	Art. no.	P. Qty.
Aerosol canister	4.1 kg	0893 100 011	1

Areas of application:

Adhesive remover specially designed for cleaning the Connecting Hose, 4 m, Art. No. 0891 602 013, the Basic Application Gun, Art. No. 0891 602 002, and the Postforming Application Gun, Art. No. 0891 602 003. Cleaning with CSA Cleaner should be carried out after two adhesive containers have been used up. Ideal for use in the workshop, various trades and industry.

Properties:

For connection to the contact spray adhesive application system. A special configuration makes CSA Cleaner especially suitable for loosening hardened adhesive residue. The cleaner flows through the application system under high pressure, making it especially effective.

Application:

Connect Application Gun, Art. No. 0891 602 002 or 0891 602 003, and the Connecting Hose, Art. No. 0891 602 013, to the cleaner. Then slowly open the valve on the container. Examine connections for leaks. Actuate pistol in bursts. After rinsing, close the valve on the container and release the remaining pressure using the application gun. While cleaning, catch any material which comes out and dispose of it properly. Should the spray angle be impaired by hardened adhesive residue on the brass-colored main nozzle, clean it

thoroughly with a lint-free cloth and CSA Cleaner.

Remarks:

Store and use tank in a well-ventilated area. Tank is under pressure. Protect from sunlight and temperatures over +50°C. Recommended storage temperature is +10°C to +30°C. Shake tank well before use. Check material and paint compatibility before use. Always carry out preliminary tests in non-visible locations! Hardened contact adhesions can be attacked by contact with CSA Cleaner. In case of contact with paint, the reaction time is max. 2 hours. Only separate hose from tank if relieved of pressure and drained and with the valve on the container closed! Observe information in the operating instructions.

Technical data	
Color	Yellowish to amber
Cleaner base	Organic cleaning substances
Density	0.85 - 0.90 g/cm ³
Flash point	-50°C
Shelf life	15 months

Additional items:

Application Gun
Art. No. 0891 602 0..

Connecting Hose, 4 m
Art. No. 0891 602 013

Cleaning Paper, e.g. "Wipe 500 Tex"
Art. No. 0899 800 88

With this information we want to advise you to the best of our knowledge based on our tests and experience. Preliminary testing required! For further information, see the technical data sheet.