

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : V-BELT SPRAY - 400 ML  
Product code : 0893230

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricants and lubricant additives

#### 1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG  
Reinhold-Würth-Str. 12-17  
74653 Künzelsau  
Telephone : +49 794015 0  
Telefax : +49 794015 10 00  
E-mail address of person responsible for the SDS : prodsafe@wuerth.com

#### 1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3	H336: May cause drowsiness or dizziness.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing spray.  
P273 Avoid release to the environment.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:  
Hydrocarbons, C6, isoalkanes, <5% n-hexane

### 2.3 Other hazards

May displace oxygen and cause rapid suffocation.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Not Assigned  01-2119484651-34	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 30 - < 50
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not Assigned  01-2119475515-33	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 30

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Not Assigned 01-2119486291-36	Flam. Liq. 2; H225 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 2,5 - < 10
--	----------------------------------	--	---------------

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.  
May cause drowsiness or dizziness.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate contain-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

ment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |   |
|-------------------------|---|---|
| Technical measures      | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.   |
| Local/Total ventilation | : | Use with local exhaust ventilation.<br>Use only in an area equipped with explosion proof exhaust ventilation.   |
| Advice on safe handling | : | Do not get on skin or clothing.<br>Do not breathe vapours or spray mist.<br>Do not swallow.<br>Avoid contact with eyes.<br>Handle in accordance with good industrial hygiene and safety practice.<br>Keep away from heat and sources of ignition.<br>Take precautionary measures against static discharges.<br>Take care to prevent spills, waste and minimize release to the environment.<br><br>Do not spray on an open flame or other ignition source. |
| Hygiene measures        | : | Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.  |

### 7.2 Conditions for safe storage, including any incompatibilities

- |   |   |  |
|---|---|--|
| Requirements for storage areas and containers | : | Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sunlight. |
| Advice on common storage                      | : | Do not store with the following product types:<br>Self-reactive substances and mixtures<br>Organic peroxides<br>Oxidizing agents<br>Flammable solids   |

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives

Storage class (TRGS 510) : 2B, Aerosol cans and lighters  
Storage period : > 24 Months  
Recommended storage temperature : 15 - 35 °C  
Other data : Keep away from direct sunlight. Keep away from heat.

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Not Assigned	AGW	1.500 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not Assigned	TWA	500 ppm 2.085 mg/m <sup>3</sup>	2000/39/EC
Further information	Indicative			
		AGW	500 ppm 2.100 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	1;(I)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Butane	106-97-8	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

	for the health (MAK-commission).			
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	Not Assigned	AGW	1.500 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	2085 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	300 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	447 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	149 mg/kg bw/day
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Consumers	Ingestion	Long-term systemic effects	149 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5306 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	1377 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1301 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	5306 mg/m <sup>3</sup>

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

clics, <5% n-hexane				
	Workers	Skin contact	Long-term systemic effects	13964 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1131 mg/m3
	Consumers	Skin contact	Long-term systemic effects	1377 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1301 mg/kg bw/day

### 8.2 Exposure controls

#### Engineering measures

Minimize workplace exposure concentrations.  
Use only in an area equipped with explosion proof exhaust ventilation.  
Use with local exhaust ventilation.

#### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Safety glasses

#### Hand protection

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : 0,7 mm  
Directive : DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Wear the following personal protective equipment:  
Flame retardant antistatic protective clothing.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : aerosol



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

Propellant : Butane, Propane, Isobutane

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 8,5 %(V)

Lower explosion limit / Lower flammability limit : 0,8 %(V)

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Density : 0,673 g/cm<sup>3</sup> (20 °C)

Solubility(ies)  
Water solubility : partly miscible, immiscible

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 365 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Particle size : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

Self-ignition : The substance or mixture is not classified as self heating.

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): 16.750 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): 259,354 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

Acute dermal toxicity : LD50 (Rabbit): > 3.350 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2.800 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 3.350 mg/kg  
Remarks: Based on data from similar materials

### Skin corrosion/irritation

Causes skin irritation.

#### Components:

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: Skin irritation

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Species: Rabbit  
Result: Skin irritation  
Remarks: Based on data from similar materials

### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Species: Rabbit

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

Method: OECD Test Guideline 404  
Result: No skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials

#### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Test Type: Local lymph node assay (LLNA)  
Exposure routes: Skin contact  
Species: Mouse  
Result: negative  
Remarks: Based on data from similar materials

#### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Test Type: Maximisation Test  
Exposure routes: Skin contact  
Species: Guinea pig  
Result: negative  
Remarks: Based on data from similar materials

#### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Test Type: Local lymph node assay (LLNA)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

- Genotoxicity in vivo
- : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials
  - : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

### **Carcinogenicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 2 yr  
Result: negative  
Remarks: Based on data from similar materials

Species: Mouse  
Application Route: inhalation (vapour)  
Exposure time: 2 yr  
Result: negative  
Remarks: Based on data from similar materials

#### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species: Rat  
Application Route: inhalation (vapour)  
Exposure time: 2 yr  
Result: negative  
Remarks: Based on data from similar materials

Species: Mouse  
Application Route: inhalation (vapour)  
Exposure time: 2 yr  
Result: negative  
Remarks: Based on data from similar materials

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

- Effects on fertility
- : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

### STOT - single exposure

May cause drowsiness or dizziness.

#### Components:

### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment: May cause drowsiness or dizziness.

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Assessment: May cause drowsiness or dizziness.

### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Assessment: May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

### Repeated dose toxicity

#### Components:

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Species: Rat, male  
NOAEL: 10,504 mg/l  
Application Route: inhalation (vapour)  
Exposure time: 90 Days  
Remarks: Based on data from similar materials

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species: Rat  
NOAEL: 12,47 mg/l  
Application Route: Inhalation  
Exposure time: 90 Days  
Remarks: Based on data from similar materials

##### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Species: Rat, male  
NOAEL: 10,504 mg/l  
LOAEL: 31,652 mg/l  
Application Route: inhalation (vapour)  
Exposure time: 91 Days  
Remarks: Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

##### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 - 10 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: > 0,1 - 1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13,4 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l  
Exposure time: 72 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,17 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 211  
Remarks: Based on data from similar materials

### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 12 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Selenastrum capricornutum (green algae)): 0,1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

## 12.2 Persistence and degradability

### Components:

#### Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

#### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### 12.3 Bioaccumulative potential

#### Components:

##### **Hydrocarbons, C6, isoalkanes, <5% n-hexane:**

Partition coefficient: n- : log Pow: 3,6  
octanol/water

##### **Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Partition coefficient: n- : log Pow: > 4  
octanol/water Remarks: Based on data from similar materials

##### **Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n- : log Pow: > 3 - < 4  
octanol/water Remarks: Based on data from similar materials

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

Waste Code : The following Waste Codes are only suggestions:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

used product, unused product  
160504, gases in pressure containers (including halons) containing dangerous substances

uncleaned packagings  
150110, packaging containing residues of or contaminated by dangerous substances

Acc. Packaging Ordinance properly emptied packaging:  
Properly emptied, non-contaminated packaging of non-hazardous products can be supplied to a system for the collection of sales packaging.

### SECTION 14: Transport information

#### 14.1 UN number

ADN	:	UN 1950
ADR	:	UN 1950
RID	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

#### 14.2 UN proper shipping name

ADN	:	AEROSOLS
ADR	:	AEROSOLS
RID	:	AEROSOLS
IMDG	:	AEROSOLS (Hydrocarbons, C6, isoalkanes, <5% n-hexane, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics)
IATA	:	Aerosols, flammable

#### 14.3 Transport hazard class(es)

ADN	:	2
ADR	:	2
RID	:	2
IMDG	:	2.1
IATA	:	2.1

#### 14.4 Packing group

ADN	:	
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
ADR	:	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

---

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

### RID

Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : yes

### ADR

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

## 14.6 Special precautions for user

Not applicable

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version 3.5      Revision Date: 27.06.2017      SDS Number: 430575-00006      Date of last issue: 05.04.2017  
Date of first issue: 11.06.2010

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

Water contaminating class (Germany) : WGK 2 water endangering  
Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 97,70 %, 657,5 g/l  
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

#### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Aquatic Chronic	: Chronic aquatic toxicity
Asp. Tox.	: Aspiration hazard
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2000/39/EC / TWA	: Limit Value - eight hours
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## V-BELT SPRAY - 400 ML

Version	Revision Date:	SDS Number:	Date of last issue: 05.04.2017
3.5	27.06.2017	430575-00006	Date of first issue: 11.06.2010

---

for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN