



Spot 8000

Multifunctional spot welding device with air-cooled spotting tongs and TE 95 digital dual control.

Suitable for conventional joining of metal sheets.

Art. No. 0691 500 230

- Spotter with pneumatic tongs with 200 daN electrode force at 107 mm arm length.
- For spot welding and dent removal work on conventional car body sheets.
- TE 95 dual control runs two independent welding programs for different tools.
- Greater operating comfort thanks to simultaneous connection of spot welding tongs and multifunctional gun, resulting in no time wasted changing tools.

Includes

- TE 95 dual control with pulse programme and programme for metal sheets with paint residues.
- Compressed air tongs with 200 daN electrode force (at 107 mm arm length) with integrated pressure sensor, cable length 2,000 mm.
- Multifunctional gun with cable length 2,000 mm for dent removal, compressing, pulling-in of metal sheets, tack-welding and impact spotting.
- Earth cable with clamp; cable length 2,000 mm.
- Compressed air water-cooling.
- Arm pair straight 107 mm.
- Trolley with holder the arm pairs.
- Bracket with balancer and adjustable hanger for spot welding tongs.
- Dent removal accessory kit.
- Sliding pull-out hammer.

Mains power	No. of phases	Nominal power	Maximum welding power	Short-circuit secondary current	Current at 100% ED	Secondary voltage
400 V/50 Hz	1	10 kVA	50 kVA	8 kA	0.88 kA	8 V
Slow blow fuse	Mains cable cross-section, L=15 m	Heat class	Protection class	Control current connection	Net weight	Dimensions
25 A	3 x 6 mm ²	F	IP 21	8 bar	105 kg	64 x 46 x 100 cm



3-Piece Electrode Set

Water-cooled with electrode caps, arm Ø 20 mm

Art. No. 0691 500 231



0691 500 212
Semicircular

0691 500 213
Conical

0691 500 214
Eccentric



0691 500 215
Curved and flat

0691 500 216
Spherical
R = 50 mm

0691 500 217
12 mm curved

0691 500 218
Special electrode
45 mm

Replacement Electrode Caps

Water-cooled for Spot 9000 and Spot 8000

Qualified contact persons:

From Monday to Friday 8.00 a.m. to 17.00 p.m. (CET) your questions will be answered by one of our specialists under the following number: +49 72 60 / 92 04 92!