according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ROST OFF CRAFTY - 300 ML

Product code : 0893130

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Cleaning agent, Detergent

stance/Mixture

1.3 Details of the supplier of the safety data sheet

Company : Adolf Wuerth GmbH & Co. KG

Reinhold-Würth-Str. 12-17

74653 Künzelsau

Telephone : +49 794015 0

Telefax : +49 794015 10 00

E-mail address of person

responsible for the SDS

: prodsafe@wuerth.com

### 1.4 Emergency telephone number

Giftnotrufzentrale Berlin +49 30 30686 790. Gesellschaft (07:00 – 18:00 Uhr) +49 794015 2552

### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-

posure, Category 3

H336: May cause drowsiness or dizziness.

Chronic aquatic toxicity, Category 3 H412: Harmful to aquatic life with long lasting ef-

fects.

#### 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin dryness or

cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

#### 2.3 Other hazards

None known.

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

#### **Hazardous components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not Assigned 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Chronic 3; H412	>= 50 - < 70
(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine	110-25-8 203-749-3 01-2119488991-20	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Acute 1;	>= 0,25 - < 1

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

		H400	
Heptadecenyl imidazoline ethanol	95-38-5 202-414-9	Acute Tox. 4; H302 Skin Corr. 1C; H314 Eye Dam. 1; H318 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1;	>= 0,25 - < 1
		H410	

For explanation of abbreviations see section 16.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes serious eye irritation.

May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Flash back possible over considerable distance. Vapours may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides

### 5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice and personal protective equip-

ment recommendations.

#### 6.2 Environmental precautions

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

harriers)

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapours/mists with a water

spray jet.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

Local/Total ventilation : Use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe vapours or spray mist.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

oractice

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the

environment.

Do not spray on an open flame or other ignition source.

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Do not pierce or burn, even after use. Keep cool. Protect from sun-

light.

Advice on common storage : Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

**Explosives** 

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

Recommended storage tem-

perature

< 50 °C

7.3 Specific end use(s)

Specific use(s) : No data available

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	Not As- signed	AGW	600 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	2;(II)			
Further information			oon solvent mixtures, Comm 2.9 of the TRGS 900	ssion for dan-
Isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
White mineral oil (petroleum)	8042-47-5	AGW (Alveolate fraction)	5 mg/m3	DE TRGS 900
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission)., When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Propane	74-98-6	AGW	1.000 ppm 1.800 mg/m3	DE TRGS 900
Peak-limit: excursion factor (catego-	4;(II)			

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

ry)					
Further information	Senate commission for the review of compounds at the work place dangerous				
	for the health	for the health (MAK-commission).			
White mineral oil	8042-47-5	AGW (Alveolate	5 mg/m3	DE TRGS	
(petroleum)		fraction)		900	
Peak-limit: excur-	4;(II)				
sion factor (catego-					
ry)					
Further information	Senate commission for the review of compounds at the work place dangerous				
	for the health (MAK-commission)., When there is compliance with the OEL				
	and biological tolerance values, there is no risk of harming the unborn child				
Butane	106-97-8	AGW	1.000 ppm	DE TRGS	
			2.400 mg/m3	900	
Peak-limit: excur-	4;(II)				
sion factor (catego-					
ry)					
Further information	Senate commission for the review of compounds at the work place dangerous				
	for the health (MAK-commission).				

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health ef- Value fects	
(Z)-N-Methyl-N-(1- oxo-9- octadecenyl)glycine	Workers	Inhalation	Long-term systemic effects	0,2 mg/m3
	Workers	Inhalation	Acute systemic effects	18 mg/m3
	Workers	Inhalation	Long-term local ef- fects	0,01 mg/m3
	Workers	Inhalation	Acute local effects	18 mg/m3
	Workers	Skin contact	Long-term systemic effects	10 mg/kg bw/day
	Workers	Skin contact	Acute systemic ef- fects	100 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,1 mg/m3
	Consumers	Inhalation	Acute systemic effects	9 mg/m3
	Consumers	Inhalation	Long-term local ef- fects	5 μg/m3
	Consumers	Inhalation	Acute local effects	9 mg/m3
	Consumers	Skin contact	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Skin contact	Acute systemic ef- fects	50 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	5 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	92 mg/kg bw/day
Heptadecenyl imidaz- oline ethanol	Workers	Inhalation	Long-term systemic effects	0,46 mg/m3
	Workers	Inhalation	Acute systemic ef-	14 mg/m3

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

		fects	
Workers	Skin contact	Long-term systemic effects	0,06 mg/kg bw/day
Workers	Skin contact	Acute systemic effects	2 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
(Z)-N-Methyl-N-(1-oxo-9-	Fresh water sediment	0,43 μg/l
octadecenyl)glycine		
	Marine sediment	0,043 μg/l
	Intermittent use/release	4,3 μg/l
	Sewage treatment plant	13 mg/l
Heptadecenyl imidazoline etha- nol	Fresh water	0,0003 mg/l
	Marine water	0,000003 mg/l
	Intermittent use/release	0,0003 mg/l
	Sewage treatment plant	0,27 mg/l
	Fresh water sediment	0,376 mg/kg
	Marine water	0,0376 mg/kg
	Soil	0,075 mg/kg

### 8.2 Exposure controls

### **Engineering measures**

Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof exhaust ventilation.

Use with local exhaust ventilation.

# Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Safety goggles

Hand protection

Material : Nitrile rubber
Break through time : 480 min
Glove thickness : 0,45 mm
Directive : DIN EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Self-contained breathing apparatus

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Appearance : Aerosol containing a liquefied gas

Propellant : Isobutane, Propane, Butane

Colour : clear

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

Not applicable

Flash point : 24 °C

Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

8,5 %(V)

Lower explosion limit / Lower

flammability limit

0,6 %(V)

Vapour pressure : Not applicable

Relative vapour density : Not applicable

Relative density : No data available

Density : 0,78 g/cm3

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : Not applicable

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

octanol/water

Auto-ignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Not classified as a reactivity hazard.

#### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Extremely flammable aerosol.

Vapours may form explosive mixture with air.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Can react with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

Information on likely routes of : Inhalation exposure Skin conta

Skin contact

Ingestion Eye contact

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

### **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

### **Components:**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.951 mg/m3

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 1,01 - 1,85 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

#### Heptadecenyl imidazoline ethanol:

Acute oral toxicity : LD50 (Rat): 1.265 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

#### Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

#### Components:

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species: Rabbit

Result: Mild skin irritation

Assessment: Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Skin irritation

### Heptadecenyl imidazoline ethanol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Corrosive after 1 to 4 hours of exposure

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### **Components:**

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Remarks: Based on data from similar materials

### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species: Rabbit

Result: Irreversible effects on the eye

### Heptadecenyl imidazoline ethanol:

Species: Rabbit

Result: Irreversible effects on the eye

#### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

### Respiratory sensitisation

Not classified based on available information.

### **Components:**

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

Remarks: Based on data from similar materials

### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Test Type: Maximisation Test Exposure routes: Skin contact

Species: Guinea pig Result: negative

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

### Heptadecenyl imidazoline ethanol:

Test Type: Maurer optimisation test Exposure routes: Skin contact

Species: Guinea pig Result: negative

### Germ cell mutagenicity

Not classified based on available information.

### **Components:**

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion

Result: negative

Germ cell mutagenicity- As-

sessment

Classified based on benzene content < 0.1% (Regulation (EC)

1272/2008, Annex VI, Part 3, Note P)

#### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

#### Heptadecenyl imidazoline ethanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

### Carcinogenicity

Not classified based on available information.

#### **Components:**

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species: Rat

Application Route: inhalation (vapour)

Exposure time: 105 weeks

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

### Reproductive toxicity

Not classified based on available information.

#### Components:

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

Effects on foetal develop-

ment

Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 421

Result: negative

### Heptadecenyl imidazoline ethanol:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

#### STOT - single exposure

May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

#### **Components:**

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Assessment: May cause drowsiness or dizziness.

#### STOT - repeated exposure

Not classified based on available information.

#### Components:

### Heptadecenyl imidazoline ethanol:

Exposure routes: Ingestion

Target Organs: Gastrointestinal tract, thymus

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to

100 mg/kg bw.

#### Repeated dose toxicity

#### **Components:**

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Species: Rat

NOAEL: 10.186 mg/m3

Application Route: inhalation (vapour)

Exposure time: 13 Weeks

### (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Species: Rat

NOAEL: > 0.06 mg/l

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 Days

Method: OECD Test Guideline 412

### Heptadecenyl imidazoline ethanol:

Species: Rat NOAEL: 20 mg/kg LOAEL: 100 mg/kg

Application Route: Ingestion Exposure time: 31 - 51 Days

Method: OECD Test Guideline 422

### **Aspiration toxicity**

Not classified based on available information.

#### Components:

## Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

### **Components:**

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 9,3 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,43 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 6,3 mg/l

Exposure time: 72 h

M-Factor (Acute aquatic tox-

icity)

: 1

Toxicity to microorganisms : NOEC : 10 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

#### Heptadecenyl imidazoline ethanol:

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,3 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,163 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 0,03 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC10 (Desmodesmus subspicatus (green algae)): 0,014 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic tox-

icity)

10

Toxicity to microorganisms : IC50 : 26 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

M-Factor (Chronic aquatic

toxicity)

1

### 12.2 Persistence and degradability

#### Components:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 89 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

(Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 85,2 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Heptadecenyl imidazoline ethanol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1 % Exposure time: 28 d

Method: OECD Test Guideline 301B

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

### 12.3 Bioaccumulative potential

#### **Components:**

# (Z)-N-Methyl-N-(1-oxo-9-octadecenyl)glycine:

Partition coefficient: n-

octanol/water

: log Pow: 3,5 - 4,2

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

Not relevant

#### 12.6 Other adverse effects

No data available

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product. Please ensure aerosol cans are sprayed completely empty

(including propellant)

Waste Code : The following Waste Codes are only suggestions:

used product

160504, gases in pressure containers (including halons) con-

taining dangerous substances

unused product

160504, gases in pressure containers (including halons) con-

taining dangerous substances

uncleaned packagings 150104, metallic packaging

Acc. Packaging Ordinance properly emptied packaging: Properly emptied, non-contaminated packaging of nonhazardous products can be supplied to a system for the col-

lection of sales packaging.

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2017

 5.1
 19.05.2017
 549157-00006
 Date of first issue: 11.06.2010

# **SECTION 14: Transport information**

### 14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

### 14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

### 14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

# 14.4 Packing group

### ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

#### ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

### **RID**

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

#### **IMDG**

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

**SECTION 15: Regulatory information** 

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EC) No 850/2004 on persistent organic pol-

lutants

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

P3a

according to Regulation (EC) No. 1907/2006



# **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

Quantity 1 Quantity 2
FLAMMABLE AEROSOLS 150 t 500 t

34 Petroleum products: (a) 2.500 t 25.000 t

gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

18 Liquefied extremely flam- 50 t 200 t

mable gases (including LPG) and natural gas

Water contaminating class : WGK 1 slightly water endangering

(Germany) Classification according VwVwS, Annex 4.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 90,06 %, 757 g/l

Remarks: VOC content excluding water

Regulation (EC) No. : 30 % and more: Aliphatic hydrocarbons 648/2004, as amended less than 5 %: Non-ionic surfactants

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

## **Full text of H-Statements**

H226 : Flammable liquid and vapour.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways. H314 : Causes severe skin burns and eye damage.

H315 : Causes skin irritation.

H318 : Causes serious eye damage.

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

Version 5.1	Revision Date: 19.05.2017		DS Number: 19157-00006	Date of last issue: 08.02.2017 Date of first issue: 11.06.2010	
H332 H336		:	Harmful if inhaled May cause drows	d. siness or dizziness.	
H373		:	: May cause damage to organs through prolonged or repeated exposure if swallowed.		
H400		:	: Very toxic to aquatic life.		
H410		:	Very toxic to aquatic life with long lasting effects.		
H412			Harmful to aquatic life with long lasting effects.		

#### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute
Aquatic Chronic
Asp. Tox.
Eye Dam.
Flam. Liq.
Skin Corr.
Skin Irrit.

Acute aquatic toxicity
Chronic aquatic toxicity
Aspiration hazard
Serious eye damage
Flammable liquids
Skin corrosion
Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations: vPvB - Very Persistent and Very Bioaccumulative

according to Regulation (EC) No. 1907/2006



### **ROST OFF CRAFTY - 300 ML**

Version Revision Date: SDS Number: Date of last issue: 08.02.2017 5.1 19.05.2017 549157-00006 Date of first issue: 11.06.2010

**Further information** 

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment

Eye Irrit. 2 H319 Calculation method STOT SE 3 H336 Calculation method Aquatic Chronic 3 H412 Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DE / EN