

## REMOVABLE SPRAY ADHESIVE



**Removable spray adhesive for the attachment of lightweight materials**

**Can be applied repeatedly**

Can be re-adhered/corrected repeatedly after removal

**No adhesive residues**

Residue-free removal

**Colorless**

Adhesive film can't be seen thanks to transparent nature

**Additional surface spray head**

**Non-coloring**

**No ridging**

**No adhesive penetration**

**Silicone-free**

<b>Art. No.</b>	<b>0893 100 20</b>	
<b>P.</b>	1	12
<b>Contents</b>	400 ml	400 ml
<b>Chemical basis</b>	Acrylic resin	Acrylic resin
<b>Color</b>	Transparent	Transparent
<b>Min./max. flash-off time</b>	20 - 30 s	20 - 30 s
<b>Min./max. working temperature</b>	15 to 25 °C	15 to 25 °C
<b>Yield (area)</b>	4 m <sup>2</sup>	4 m <sup>2</sup>
<b>Suitable for storage from time of manufacture</b>	18 months	18 months

Supplement to Art. No.:	Designation	Art. No.
0893 100 20	Industry Clean Cleaner	<b>0893 140</b>
	Softex/Softex-light Cleaning Cloth	<b>0899 800 901</b>

### Application

For the adhesion of templates, advertisement posters, decorations at trade fairs, attachment of layouts and technical drawings, model construction, re-closing of boxes etc.

For adhering paper, cardboard, cloth, films and Styrofoam to metals, wood, glass, plastics etc.

### Note

Turn can upside down and spray until valve is empty after use.

### Instructions

Spray adhesive is sprayed onto one side. Test the suitability of the adhesive beforehand. The surface nozzle, which is integrated in the cap, is suitable for larger surfaces. Long-term adhesion is possible with two-sided, thick application. Adhesive residue can be cleaned with Industry Clean.

This information is only a recommendation based on our experience. Preliminary testing required! When using the product, both the technical data sheet and the specifications of the applicable regulations must be complied with.