

EPDM OUTDOOR SEALING TAPE
EPDM SK OUTDOOR SEALING TAPE
EPDM BUTYL OUTDOOR SEALING TAPE
EPDM BUTYL INDOOR SEALING TAPE

Width in mm	Roll length in m	Art. No. EPDM Outdoor SealingTape	Art. No. EPDM SK Outdoor Sealing Tape	Art. No. EPDM Butyl Outdoor Sealing Tape	Art. No. EPDM Butyl Indoor Sealing Tape	P. Qty.
150	20	0875 350 150	0875 350 151	0875 350 152	0875 350 153	6
200	20	0875 350 200	0875 350 201	0875 350 202	0875 350 203	4
250	20	0875 350 250	0875 350 251	0875 350 252	0875 350 253	4
300	20	0875 350 300	0875 350 301	0875 350 302	0875 350 303	3
400	20	0875 350 400	0875 350 401	0875 350 402	0875 350 403	2
500	20	0875 350 500	0875 350 501	0875 350 502	0875 350 503	2

Technical Data				
Name	EPDM Outdoor Sealing Tape	EPDM SK Outdoor Sealing Tape	EPDM Butyl Outdoor Sealing Tape	EPDM Butyl Indoor Sealing Tape
Version	No self-adhesion	With self-adhesion	With butyl strips	With butyl strips
Chemical basis	EPDM rubber	EPDM rubber	EPDM rubber	PIB rubber
Color	Black	Black	Black	Black
Material thickness	0.6 mm	0.6 mm	1.2 mm	1.2 mm
Maximum elongation at tear	> 300%	> 300%	> 300%	> 300%
Temperature-resistance	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C
Water-vapor-equivalent air layer thickness	Sd = approx. 3.5 m	Sd = approx. 3.5 m	Sd = approx. 7.6 m	Sd = approx. 300 m
Water-vapor diffusion resistance coefficient	μ = approx. 5,882	μ = approx. 5,882	μ = approx. 5,882	μ = approx. 270,000
UV resistance	given	given	given	given
Bitumen compatibility	given	given	given	given